



深圳市兆威机电股份有限公司

地址:深圳市宝安区松岗街道燕罗工业区朝阳路兆威工业园
电话:0086-755-2732 2645
传真:0086-755-2732 3949
邮编:518105
网址:www.szzhaowei.com
邮箱:sales@szzhaowei.net

兆威企业(香港)有限公司

地址:中国香港中环德辅道西60-64号荣裕商业大厦1005室
电话:00852-63264597
传真:00852-63264597
电邮:sales@zwgearbox.com

ZW Drive GmbH

ADD: Alte Marktoberdorfer Straße 14, 87616 Marktoberdorf
TEL: +49 89 6600 2375
E-mail: kontakt@zw-drive.com

SHENZHEN ZHAOWEI MACHINERY & ELECTRONICS CO., LTD.

ADD: Zhaowei Industrial Park, Chaoyang Rd., Yanluo Industrial Zone, Songgang Str.,
Bao'an Dist., Shenzhen, 518127, Guangdong, China
TEL: 0086-755-2732 2645
FAX: 0086-755-2732 3949
Website: <http://www.zwgearbox.com>
E-mail:sales@zwgearbox.com

ZHAOWEI ENTERPRISE (H.K.) COMPANY LIMITED

ADD: Room 1005, Wing Yue Building, 60-64 Des Voeux Road
West, Hong Kong, China.
TEL: 00852-63264597
FAX: 00852-63264597
E-mail:sales@zwgearbox.com



微信公众号



兆威官网

愿景和使命 | VISION & MISSION

致力微型驱动领域进步，共创智能美好生活

Advancing the Micro Drive Industry, Creating a Better Smart Life

核心价值观 | CORE VALUE

创造价值，坚持创新，持续奋斗，追求卓越


Create Value, Innovate with Drive, Strive to Thrive, Aim to Excel



微型驱动系统制造商
Micro Drive System Manufacturer

股票简称：兆威机电 股票代码：003021
Stock Abbreviation: ZHAOWEI Machinery & Electronics Stock Code: 003021

About ZHAOWEI	一、关于兆威	01-12
Company Profile	公司简介	03-04
Company Milestones	发展历程	05-06
ZHAOWEI Honor	兆威荣誉	07-08
Our Clients	合作伙伴	09-10
Quality System & Certification	品质认证和体系	11-12
R&D Capability	二、研发实力	13-21
R&D Teams	研发团队	15-16
Patents & Innovation	专利和技术创新	17
Gearbox Design	齿轮箱设计	18
Mold Development	模具开发	19
Gear Technology	齿轮技术	20
Micro Motor Control Module Development	微型电控模块开发	21
Fine Machining & Quality Control	三、精密加工与品质控制	22-34
Fine Machining	精密加工	23-26
Quality Control	品质控制	27-34
Production Capability	四、生产实力	35-43
MES System	MES系统	37
Parts Production Lines	零件生产线	38-40
Assembly Lines	组装生产线	41-42
PCBA Production Lines	PCBA生产线	43
Product Series	五、产品体系	44-48
Intelligent Drive Systems	六、智能驱动系统	49-104
Automotive Electronics	汽车电子	51-60
Industrial Automation	工业自动化	61-65
Medical Micro Drive Systems	智慧医疗	66-70
Smart Home	智能家居	71-79
Consumer electronics	消费电子	80-93
Robot	机器人	94-96
Standard Gearboxes	七、标准齿轮箱系列	97-158
SMD planetary gearbox	SMD行星齿轮箱	99-120
MD planetary gearbox	MD行星齿轮箱	121-134
PD planetary gearbox	PD行星齿轮箱	135-146
Zero backlash gearbox	零背隙齿轮箱	147-148
PL Right-Angle Gear Motor	PL直角电机齿轮箱	149-151
MC Spur Gearbox	MC正传动减速箱	152-158
Micro Motor	八、电机系列	159-171
MC brushless DC coreless motor	MC系列无刷直流空心杯电机	161-165
MP brushed DC motor	MP有刷直流电机	166-169
MC stepper motor	MC步进电机	170-171
Electronic control board	九、电控系统	172-180
CB-ST encoder	CB-ST编码器	173-177
Electronic Control Boards	电控板	178-180



Micro Drive System Manufacturer
Provide Integrated Drive Solutions

微型驱动系统制造商
为您提供系统化的解决方案

公司简介

Company Profile

深圳市兆威机电股份有限公司（以下简称“兆威”）成立于2001年，是一家集设计、研发、制造于一体的微型传动和微型驱动系统方案解决商。兆威是国家高新技术企业，总部位于广东省深圳市，注册资本2.3亿元，股票代码：003021。兆威产品主要应用于智慧医疗、工业自动化、智慧出行、智能消费、机器人等领域。

兆威在深圳、上海、苏州、东莞、香港、德国、美国等地设有3家分公司和7家子公司。兆威共有员工2200多人，在深圳有办公和制造厂房面积6万平方米。已在东莞建成微型传动系统研发和制造基地，正在苏州建设微型驱动系统产业园。

兆威先后获得广东省微型齿轮传动工程技术研究中心、深圳市智能机器人微型驱动系统工程研究中心、国家级企业技术中心、机械工业微型传动系统工程技术研究中心、国家制造业单项冠军、国家知识产权优势企业、广东省机器人骨干企业、广东省知识产权示范企业等资质认定，是国家数字化设计与制造创新中心参与单位；荣获国家科技进步二等奖、广东省科技进步一等奖、中国专利奖、中国机械工业科技进步特等奖、中国工业大奖表彰奖、中国好设计金奖、全国机械工业产品质量创新大赛金奖等荣誉奖项；承担了多项国家、省、市、区各级科技计划项目。

兆威已通过ISO9001、ISO14001、ISO45001、IATF16949、ISO13485、知识产权、两化融合、智能制造能力成熟度（三级）、CMMI L3等体系认证，建立了科学管理和企业现代化体系。公司重视科技实力和自主创新，拥有一支500余人的研发工程团队，形成了从研发、设计、装配到检测的系统性、全方位的人才队伍。参与制定国家标准3项，主持制定团体标准1项，参与制定团体标准2项。

兆威人秉持着“创造价值，坚持创新，持续奋斗，追求卓越”的核心价值观，持续为行业提供优质产品和服务。未来，兆威将继续拥抱智能时代，以“致力微型驱动领域进步，共创智能美好生活”为愿景和使命，专注于微型驱动领域的理论与技术研究，不断创新和突破，推动微型驱动产业及万物互联生态链的发展进步，赋能多场景、高品质的智能科技应用，实现人们生活更加便捷、舒适、美好！

Shenzhen Zhaowei Machinery & Electronics Co., Ltd. (Zhaowei), established in 2001, is a micro transmission and drive system solution provider that integrates design, research, development, and manufacturing. Zhaowei is recognized as a Chinese high-tech enterprise, headquartered in Shenzhen, Guangdong with a registered capital of 238.9408 million RMB and stock code: 003021. The company's products are primarily applied in smart healthcare, industrial equipment, automotive electronics, smart home solutions, consumer electronics, and robotics.

Zhaowei operates 3 branch offices and 7 subsidiaries located in Shenzhen, Shanghai, Suzhou, Dongguan, Hong Kong, Germany, and the United States. The company employs over 2,200 people and has a combined office and manufacturing space of 60,000 square meters in Shenzhen. Zhaowei has established a micro transmission system R&D and manufacturing base in Dongguan and is in the process of constructing a micro drive system industrial park in Suzhou.

The company has been recognized with numerous accolades, including certifications as the Guangdong Provincial Micro Gear Transmission Engineering Technology Research Center, Shenzhen Intelligent Robot Micro Drive System Engineering Research Center, National Enterprise Technology Center, and Mechanical Industry Micro Transmission System Engineering Technology Research Center. Zhaowei is a recipient of prestigious titles such as National Manufacturing Champion, National Intellectual Property Advantage Enterprise, Guangdong Provincial Key Robotics Enterprise, and Guangdong Provincial Intellectual Property Model Enterprise. It is also an active participant in the National Digital Design and Manufacturing Innovation Center.

Zhaowei's awards include the National Science and Technology Progress Award (Second Prize), Guangdong Provincial Science and Technology Progress Award (First Prize), China Patent Award, China Machinery Industry Science and Technology Progress Special Award, China Industry Award Recognition Award, China Good Design Gold Award, and the National Machinery Industry Product Quality Innovation Competition Gold Award. The company has undertaken multiple research projects at the national, provincial, municipal, and district levels.

Zhaowei has achieved certifications such as ISO9001, ISO14001, ISO45001, IATF16949, ISO13485, Intellectual Property Management, Integration of Informationization and Industrialization, Smart Manufacturing Capability Maturity Level 3, and CMMI Level 3. It has established a modern enterprise management system emphasizing scientific rigor and technological innovation. The company's R&D team, comprising over 500 professionals, integrates expertise in research, design, assembly, and testing to deliver comprehensive, end-to-end solutions. The team has participated in formulating three national standards, led the development of one industry standard, and contributed to two additional industry standards.

Guided by the core values of "creating value, driving innovation, pursuing excellence, and continuous effort," Zhaowei is committed to providing high-quality products and services to the industry. Looking forward, Zhaowei aims to embrace the era of smart technologies with the mission of "advancing the micro drive field and creating a smarter, better future." The company is dedicated to the theoretical and technological advancement of micro drives, consistently pursuing innovation and breakthroughs to drive the development of the micro drive industry and the ecosystem of interconnected devices. Zhaowei seeks to empower diverse, high-quality intelligent applications, making life more convenient, comfortable, and enriching for everyone.



兆威长三角基地
ZHAOWEI Yangtze River Delta Base



兆威珠三角基地
ZHAOWEI Pearl River Delta Base

发展历程

Company Milestones

2001 2002-2005 2006-2009 2010-2013 2014-2017 2018-2020 2021-2022 2023-2025

公司成立

Established



精密、微小、超薄产品

Precision, micro, ultra-thin products



进军汽车行业

Entering the automotive industry



实现产值过亿

Achieving output value of over 100 million RMB



兆威产业园投入使用

ZHAOWEI Industrial Park put into use



兆威IPO上市

ZHAOWEI IPO



启动管理变革

Initiate Change Management



谱写新章

Write a new chapter



核心马达部件

Core Motor Parts

- 松下 (Panasonic)
- 三洋 (SANYO)
- 三协 (SANKYO)

精密齿轮部件

Precision Gear Parts

- 佳能 (Canon)
- 尼康 (Nikon)
- 亚洲光学 (Asia Optical)

汽车齿轮部件

Automobile Gear Parts

- 博世 (Bosch)
- 博泽 (Brose)
- 马勒 (MAHLE)
- 比亚迪 (BYD)
- 长城 (Great Wall)

微型齿轮箱

Micro Gearbox

- 华为 (HUAWEI)
- 罗森博格 (Rosenberger)
- 奥克斯 (AUX)

通讯齿轮箱

Gearbox for Communication Equipment

- 4G天线 (4G Antennas)
- 5G天线 (5G Antennas)
-

智能家居

Smart Home

- 窗帘 (Electric Curtain)
- 扫地机 (Robot Vacuum)
-

成立电控团队

Setting up electronic control team

- 马达驱动控制
- 嵌入式软件设计

汽车齿轮箱

Gearbox for Automobile

- 尾门电机 (Power Tailgate)
- EPB
-

消费电子类齿轮箱

Gearbox for Consumer Electronics Products

- 手机摄像头升降齿轮箱 (Phone Lifting Camera Gearbox)
-

微型齿轮传动

Micro Gear Transmission

驱动一体化

Drive Integration

中国机械工业科技进步特等奖

Special Prize of China Machinery Industry Science and Technology Award

中国工业大奖表彰奖

China Grand Awards for Industry of Recognition

医疗齿轮箱

Gearbox for Medical Electronics

- 胰岛素齿轮箱 (Insulin Pump)
- 清洗泵 (Pulse Lavage System)
-

广东省科技进步一等奖

The First Prize of Guangdong Province Scientific and Technological Progress Award

东莞微型传动系统研发和制造基地

Dongguan Micro Transmission System R&D and Manufacturing Base

国家制造业单项冠军

China Manufacturing Single Championship

2023年荣获中国专利奖

Won the China Patent Award in 2023

国家企业技术中心

National Enterprise Technology Center

成立美国子公司

Establish a subsidiary in the United States

兆威荣誉 ZHAOWEI Honor

国家认定 企业技术中心

The National Enterprise Technology Center of China

中国工业大奖 表彰奖

China Grand Awards for Industry (Commendation Award)

广东省科技进步 一等奖

The First Prize for Scientific and Technological Progress of Guangdong Province

国家制造业 单项冠军

Individual Championship for National Manufacturing Industry

广东省战略性新兴产业 培育企业

Enterprise of Cultivation for Strategic Emerging Industry of Guangdong Province

广东省机器人 骨干企业

Key Robot Enterprise of Guangdong Province

国家科学技术进步奖 二等奖

The Second Prize for National Scientific and Technological Progress

中国专利奖 优秀奖

China Patent Award Excellent Award

中国好设计 金奖

Chinese Good Design gold prize

中国机械工业科学技术 特等奖

Special Award for China Machinery Industry Science and Technology

国家知识产权 优势企业


Preponderant Enterprise of National Intellectual Property Rights

- 参与制定首个注射成型齿轮精度国标-GB/T 38192-2019
- 塑胶齿轮精度—国标6—10级
- 粉末冶金工艺—齿轮精度JGMA 3级
- 智能制造/CMMI 3级

- Participated in the development of the first national standard for injection molded gear precision GB/T 38192-2019
- Precision of plastic gears - National standard level 6-10
- Powder Metallurgy Process - Gear Precision JGMA Level 3



合作伙伴 Our Clients



品质认证和体系 Quality System & Certification

兆威的管理体系是企业运作的核心部分；兆威全体员工严格遵守ISO管理体系，从产品的设计、研发到生产所有的过程都严格按照体系进行；

我们致力于将产品的风险把控，在恶劣、苛刻的环境条件下，提高产品的可靠性；

我们的使命是为客户提供创新、符合客户所需的产品。

ZHAOWEI management system is the core part of company operation. All employees strictly comply with the ISO system from product design, development to production.

We are committed to controlling risks and improving product reliability under harsh environmental conditions.

Our mission is to provide innovative products that meet customer needs.



产品认证 | PRODUCT CERTIFICATION



RoHS

公司认证 | CERTIFICATES



ISO13485 (CN18/42018)

ISO9001:2015 (CN11/30731)

IATF16949 (CN11/30730.01)

ISO14001 (U006616E0153R3M)

项目管理 | PROJECT MANAGEMENT

深圳兆威机电股份有限公司承诺严格按照兆威项目管理系统为客户提供创新的、质量稳定的产品，让产品市场竞争力符合客户所需。


产品实现过程涉及:

- 产品设计确认阶段
- 顾客财产管理过程
- 产品质量先期策划过程
- 工程变更管理过程
- 产品PPAP批准过程
- 订单管理过程
- 生产及交付管理过程
- 顾客信息反馈、满意度管理过程

ZHAOWEI is committed to providing customers innovative and stable quality products in strict accordance with ZHAOWEI project management system, to ensure product market competitiveness meets customers needs.

Product Implementation Process:

- Product Design Confirmation
- Customer Property Management
- Advanced Product Quality Planning
- Engineering Change Management
- Product PPAP
- Order Management
- Production & Delivery Management
- Customer Feedback & Satisfaction Management



研发实力 R&D Capability

深圳市兆威机电股份有限公司专注于微型齿轮驱动系统的设计开发生产,为客户提供驱动解决方案。公司重视自主研发和科技创新,公司的研发团队涵盖微型传动系统、电子驱动的设计开发,产品主要涉及汽车、通讯、医疗、智能家居、美容养生&运动健康、机器人、电子产品、工业装备等领域。

ZHAOWEI specializes in designing, developing, manufacturing and providing micro gear drive systems for customers. ZHAOWEI attaches great importance to independent R&D and technological innovation, and R&D teams cover design and development of micro drive system and electric drive module. Our products are used in many fields, mainly involves automotive, communication equipment, intelligent medical equipment, smart home, beauty and health care & sports, intelligent robot, electronic product and industrial equipment.

研发团队

R&D Teams



兆威的研发团队是由教授、博士、硕士及研发工程师等组成。其中研究生和本科生占比75%，平均年龄32岁，形成了从研发、设计、制造到实验检测的系统性、综合性的开发平台。


Zhaowei's R&D team comprises professors, PhDs, postgraduates, and engineers, with postgraduate and undergraduate degree holders accounting for 75% of the team. With an average age of 32, this young and dynamic team has established a comprehensive development platform encompassing research, design, manufacturing, and experimental testing, ensuring systematic and integrated innovation.



团队构成 | Team Members

兆威的研发团队涵盖微型齿轮箱研发、控制器系统研发、精密模具设计加工、注塑与组装自动化、齿轮检测和系统测试等领域。

ZHAOWEI R&D teams cover the fields of micro gear and gearbox design and development, precision mold design and processing, injection molding and assembly automation, gear and drive system testing, etc.



研发设计团队
R&D Team

- 传动设计 Transmission Design
- 产品设计 Product Design
- 仿真验证 Simulation Verification
- 马达设计 Motor Design
- 技术开发 Technology Development



电子驱动团队
Electronic Drive Team

- 马达驱动控制 Motor Drive Control
- 嵌入式软件设计 Embedded Software Design
- 智能硬件设计 Intelligent Hardware Design




齿轮检测实验室
Gear Testing Laboratory

- 蔡司CT Zeiss CT
- 齿轮检测中心 Gear Testing Center
- 齿轮啮合测试 Gear Mesh Test
- 三坐标测量 Three-coordinate Measurement
- 热重分析仪 Thermogravimetric Analyzer




齿轮技术团队
Gear Technical Team

- 齿轮箱的研制 Gearbox Development
- 定制化研制 Customized Design
- 材料研究 Materials Research
- 模具设计 Mold Design
- 成型工艺 Molding Process



自动化团队
Automation Team

- 柔性加工技术 Flexible Machining Technology
- 注塑无人化 Injection Automation
- 组装自动化 Assembly Automation



综合测试实验室
Comprehensive Test Laboratory

- 噪声分析 Noise Analysis
- 马达综合测试 Motor Comprehensive Test
- 环境测试实验 Environmental Test
- 震动测试 Vibration Test
- 寿命测试 Life Test

专利和技术创新 Patents & Innovation

400余项专利其中微型传动关键技术专利86项,115项发明专利、37项软件著作权、23项PCT。

兆威参与并主导了多项省市科技攻关项目,在新能源汽车、4G、5G天线基站及智能机器人领域有丰富的研发和制造经验。

专利名称 Patent Name	专利类型 Patent Type	申请/授权日期 Application / Authorization Date	证书/申请编号 Certificate / Application No.
低噪音汽车尾箱减速器 Low-noise Automobile Tail Box Reducer	发明专利 Invention Authorization	2018-03-27	CN105041986BXXXX
调频组件及滤波器 FM Components and Filters	发明专利 Invention Announcement	2017-09-08	CN107146928AXXXX
小回程差角度传感器及其行星齿轮 Small Backlash Angle Sensor and Its Planetary Gears	发明专利 Invention Announcement	2017-09-08	CN107144215AXXXX
《机器人的手臂机构以及具有该手臂机构的机器人》 Robot Arm Mechanism and A Robot with the Arm Mechanism	发明专利 Invention Patent	2015-02-04	ZL201110381753.8
充电桩电子锁装置及充电桩电子锁系统 Electronic Lock Device and Lock System for EV Charger	实用新型 Utility Model	2018-05-18	CN207381641UXXXX
柔性自调位机构及机械手 Flexible Self-adjusting Mechanism and Manipulator	国际发明专利 International Invention Patent	2018-06-01	CN108098757AXXXX
天线调节装置 Antenna Tilt Adjustment Device	发明专利 Invention Announcement	2019-05-17	CN109768392A
电机控制方法及系统 Motor Control Methods and Systems	发明专利 Invention Announcement	2019-07-16	CN110022093A
离合结构和控制箱 Clutch Structure and Control Box	发明专利 Invention Announcement	2020-04-17	CN111022523A
多电机同步驱动控制方法、装置以及系统 Synchronous Drive Control Method, Device and System of Multiple Motors	发明专利 Invention Announcement	2020-06-16	CN111293927A
离合组件和控制箱 Clutch Components and Control Box	发明专利 Invention Announcement	2020-08-25	CN111577788A
摄像头推出旋转结构和电子设备 Pop-up, Rotating Camera Structures & Electronic Devices.	发明专利 Invention Announcement	2020-08-25	CN111586265A
步进电机同步驱动方法、装置、终端及存储介质 Synchronous Driving Method, Device, Terminal and Storage Medium of Stepper Motor	发明专利 Invention Announcement	2020-09-04	CN111628682A
交错轴齿轮副的传动性能测试装置 Transmission Performance Testing Device of Cross-shaft Gear Pair	发明专利 Invention Announcement	2020-08-11	CN111521389A




More than 400 patents, including 86 key technology patents for micro transmission, 115 invention patents, 37 software copyrights, 23 Patent Cooperation Treaty.

ZHAOWEI leads and participates in a number of provincial and municipal science and technology research projects, being experienced in manufacturing drive systems for new energy vehicles, 4G and 5G antenna base stations, and intelligent robots.


齿轮箱设计综合平台 | COMPREHENSIVE GEARBOX DESIGN PLATFORM

兆威自主知识产权的齿轮箱综合设计平台,可实现渐开线行星齿轮系统、锥齿轮、面齿轮等机构的自动化参数设计、齿形绘制和3D精密建模等。设计平台的特性是具有方案设计、结构设计、齿形设计、模拟分析等特点。

The gearbox design platform of ZHAOWEI's independent intellectual property rights can realize automatic parameter design, tooth shape drawing and 3D precision modeling of involute planetary gear systems, bevel gears, face gears and other mechanisms. The design platform has functions of scheme design, structural design, tooth shape design, simulation analysis, etc.



直齿圆锥齿轮副齿廓修形及精密建模
Straight bevel gear pair profile modification and precision modeling




NGW渐开线齿轮行星传动系统设计平台软件 2018SR329606
Design and Development Software of NGW Type Involute Gear Planetary Transmission System 2018SR329606

齿轮箱设计平台在进行变位系数合理的分配、啮合角优化计算、滑移率和重合度的校核。在前期设计开发阶段,优化变位系数、行星齿轮齿顶干涉校验,预防和改善齿轮箱的效率、噪音、寿命等问题。

The gearbox design platform performs reasonable allocation of modification coefficients, meshing angle optimization calculation, slip ratio and coincidence degree. In the early stage of design and development, optimize the modification coefficient and planetary gear tooth profile overlap interference to improve gearbox efficiency, noise and life.

动态仿真和有限元分析 | DYNAMIC SIMULATION AND FINITE ELEMENT ANALYSIS


在齿轮和齿轮箱设计阶段,采用运动学仿真对齿轮副运动的平稳性和局部干涉进行验证。同时采用有限元分析技术,对弧齿、锥齿轮的齿面强度进行分析校核产品的可靠性。



平行轴内、外啮合圆柱齿轮副设计平台软件 2018SR330220

Design platform software for internal and external meshing cylindrical gear pairs in parallel shafts 2018SR330220


In gear and gearbox design stage, dynamic simulation is used to verify the smoothness and local interference of gear pair movement. At the same time, finite element analysis technology is used to analyze tooth surface strength of spiral teeth and bevel gears and check product reliability.



模具开发

Mold Development

齿轮模具设计 | GEAR MOLD DESIGN



齿轮模具型腔齿形参数设计软件 2018SR627905
Gear mold cavity profile parameter design software 2018SR627905

与传统的模具设计不同,齿轮的齿厚、模数、压力角都需要结合经验数据修形,不能按收缩率直接加工,我们的优势是:根据公司设计数据自主开发了齿轮模具的型腔参数计算软件,这个软件可以直接生成齿轮参数及轮廓,用于齿轮修形、提高齿形精度。


Different from traditional mold design, the gear tooth thickness, modulus, and pressure angle need to be modified with empirical data and cannot be processed directly according to material shrinkage rate. Our advantage: the cavity parameters design software of gear molds is independently developed according to our company's design data, and the software can directly generate gear parameters and contours for gear modification and improve tooth profile precision.

3D打印冷却技术 | 3D PRINTING COOLING TECHNOLOGY

传统冷却水路采用直通式,水路的设计受到加工方式的限制,冷却不均匀、冷却效果差。兆威采用3D激光打印技术,根据产品结构,可以加工出复杂的异形冷却水路,提高了产品的冷却效果,使产品的品质更稳定,生产效率更高。




Traditional cooling water circuit adopts straight-through type, but is limited by processing method, with uneven cooling effect and poor result. ZHAOWEI adopts 3D laser printing technology, which can process complex special-shaped cooling water channels according to product structure, to improve cooling effect and achieve better product quality stability and higher production efficiency.



模流分析 | MOLD FLOW ANALYSIS

- 模流分析经验的材料研究生从事模流分析工作;
- 可以预测产品的变形、缩水、缺胶、困气等缺陷,给出对应方案;
- 可用于比较不同的设计方案,选择比较好的方案;
- 优化成型工艺参数,提高试模效率。

- Materials postgraduates with mold flow analysis experience are engaged in mold flow analysis.
- Can predict product deformation, shrinkage, lack of glue, air trap, etc. and provide corresponding solutions.
- Can compare different design schemes and choose a right scheme.
- Can optimize mold processing parameters and improve mold tryout efficiency.




型腔压力技术 | CAVITY PRESSURE TECHNOLOGY

型腔压力技术是在模具型腔内安装压力传感器,通过压力曲线可以检测注塑成型过程中型腔压力的变化,准确地反映出注塑工艺的情况,监控产品品质。

- 型腔压力技术,可快速实现型腔压力曲线与模板的匹配,提高品质一致性;
- 通过对型腔压力峰值和曲线的综合分析进行监控,来判断制品的品质状况,结合伺服机械手实现对成型不良品的自动分隔。

Cavity pressure technology is to install a pressure sensor in mold cavity, pressure curve can reflect cavity pressure change during injection process and monitor product quality.

- Cavity pressure technology can quickly match cavity pressure curve with the template to improve quality consistency.
- By comprehensive analysis of mold cavity peak pressure and pressure curve, can judge product quality, and combine with servo manipulator to automatically separate defective products.




微型电控模块开发 Micro Motor Control Module Development


聚焦微型电控，模块化定制开发

Focus On Micro Motor Control and Modular Customized Development


兆威专注微型驱动领域，在微型电机控制方面拥有完整研发体系，具备多个领域丰富开发和制造经验。

ZHAOWEI focuses on micro-drives and has a complete R&D system in micro motor control, as well as extensive development and manufacturing experience in a variety of fields.






■ 软件开发平台
Software Development Platform




■ 硬件设计平台
Hardware Design Platform



■ 完善测试标准
Complete Testing Standard



精密加工与品质控制 Fine Machining & Quality Control



深圳市兆威机电股份有限公司拥有瑞士AGIE线切割机、AGIE火花机、MAKINO、HAMAI等众多加工设备和德国蔡司三坐标、DIATEST内齿测量仪、冷热冲击实验箱、雨淋实验箱、步入式恒温恒湿室、可程式恒温恒湿箱、齿轮双面啮合仪等质检设备，ZHAOWEI专注于微型齿轮和齿轮箱精密模具设计加工、齿轮检测和传动系统测试等，为客户提供精度高、质量优的产品。

ZHAOWEI has many processing equipments such as Switzerland AGIE wire cutting machine, AGIE EDM machine, MAKINO, HAMA, etc. and Germany ZEISS three-coordinate, DIATEST internal tooth measuring instrument, cold and thermal shock testing chamber, rain and spray testing chamber, step in-class constant temperature and humidity chamber, programmable constant temperature and humidity chamber, gear double-sided meshing instrument and other quality inspection equipments. ZHAOWEI specializes in micro gear and gearbox designing and processing, gear detection and transmission system testing, and providing precision and high quality products to customers.

精密加工 Fine Machining

精加工中心 | FINE MACHINING CENTER



兆威精密加工中心拥有多种瑞士阿奇夏米尔加工设备，线切割机 CUT 1000 OilTech、CUT2000、CUT E 600、VP2、VP3；HMS500；安田YASDA 640V等加工设备。自动化精加工，使用EMAN智能管理系统及iMould自动化加工系统，为加工精度提供了保障。

ZHAOWEI fine machining center has a variety of precise machining devices, including Switzerland Agie Charmilles wire cutting machines: CUT 1000 OilTech, CUT 2000, CUT E 600, VP2, VP3; HMS500 and YASDA 640V. Automated finishing combined with the EMAN intelligent management system and the iMould automated processing system provides a guarantee for machining accuracy.

火花机自动化加工线 EDM Automated Machining Line

8台GF FORM P350火花机加1条自动化线轨
机器人组成的自动化加工项目

Including eight GF FORM P350 EDM and one automated linear slider robot, forms an automated machining line



电极自动化加工单元 Electrode Automated Machining Unit

2台HSM500CNC和1台WORKPARTNER1
电极库组成自动加工项目

Including two HSM500 CNC and one WORKPARTNER1 electrode cabinet, forms an automated electrode machining center

加工设备 | MACHINING EQUIPMENT



德国罗德施加工中心
Roders CNC (Germany)



日本安田超高速加工中心
YASDA Super High Speed CNC (Japan)



日本HAMAI滚齿机
HAMAI Gear Hobbing Machine (Japan)



瑞士阿奇火花机FORM P350
AGIE EDM FORM P350 (Switzerland)



日本牧野MAKINO火花机
MAKINO EDM (Japan)



瑞士阿奇夏米尔线切割-CUT2000
Agie Charmilles CUT 2000 (Switzerland)



瑞士阿奇线切割
AGIE WEDM (Switzerland)



瑞士米克朗CNC-HSM500
Mikron HSM 500 (Switzerland)



美国哈挺高精密CNC车削中心
Hardinge High-precision CNC (United States)



日本牧野MAKINO V33 加工中心
MAKINO V33 CNC (Japan)



瑞士加工中心-MILL P500
MILL P500 (Switzerland)



北京五轴加工中心-精雕JDGR300
JDGR300 (China)

精密加工

Fine Machining

日本HAMAI滚齿机 | JAPAN HAMAI GEAR HOBBING MACHINE

日本HAMAI哈迈为专业小型滚齿机专业制造商,在半导体材料加工,齿轮加工及测量,金属模具制作等领域提供专业化、个性化的加工设备。60SP-ELT采用卧式滚齿的特点,切削粉屑垂直排下后直接排除机外,从而大大降低了由于粉屑产生的故障,滚刀轴的转数为5000RPM,缩短加工时间,提高加工效率。可加工:直齿、斜齿、圆柱齿轮、蜗轮、链轮等。




HAMAI is a professional manufacturer of small gear hobbing machines, providing professional and personalized processing machines in the fields of semiconductor material processing, gear processing and measurement, and metal mold making. The 60SP-ELT adopts horizontal gear hobbing, the cutting powder can be directly eliminated from the machine, which can greatly reduce the faults caused by powder chips. The rotation of the hob shaft is 5,000RPM, which can shorten processing time and improve processing efficiency. Can process: straight gears, helical gears, cylindrical gears, worm gears, sprockets, etc.



瑞士阿奇夏米尔线切割机 | SWITZERLAND AGIECHARMILLES CUT 1000 OILTECH

阿奇夏米尔是欧洲精密加工的参考标准,在加工设备领域属于市场的领导者。瑞士阿奇夏米尔线切割-CUT1000拥有自动换丝(AWC)技术使Schawnog能在慢走丝线切割设备上预安装各种不同直径的电极丝(0.011mm),并将根据切割所需轮廓精度选择电极丝。IVU能够对孔定中、角部探测、两个表面的内外定中以及孔间距、定中和尺寸这类操作获的基准。



自动化精密加工系统 | AUTOMATED FINE MACHINING SYSTEMS

德国罗德斯加工中心 | GERMAN RODERS MACHINING CENTER

德国Roders(罗德斯)拥有200年模具制造经验;罗德斯在高速加工领域的领导地位,罗德斯高速加工中心除了加工速度快外,工件光洁度及精度都达到了世界水平。德国Roders机床一直以“高速加工”著称,其定位于高速,特别适合于深腔加工、清角加工、精加工等高难度工序,RXP系列机床应用了油压导轨,直线电机等技术,各项性能指标在高速铣领域遥遥领先。




Roders has 200 years mold manufacturing experience, and is in a leading position in the field of high-speed machining. In addition to fast processing speed, Roders high-speed machining center has reached world level in the finish and accuracy of workpiece. Roders machines have always been known for High-speed Machining, and are particularly suitable for deep cavity machining, corner machining, fine machining and other difficult processes. The RXP series machines apply hydraulic guide rails, linear motors and other technologies, their performance indicators are far ahead in high-speed milling field.



为实现公司自动化精加工,公司投入EMAN智能管理系统及iMould自动化加工系统。EMAN对模具从建立项目、设计、采购、工艺、计划、加工、品质、试模的全程管理,建立模具标准化。iMould系统实现CNC钢件加工自动线、CNC电极加工自动线、EDM加工自动线等,从而实现大部份模具的全自动化加工。

To realize automatic fine machining, ZHAOWEI adopts EMAN intelligent management system and iMould automated machining system. The EMAN system manages the entire process, including project set-up, mold design, material purchasing, process confirmation, production plan, machining, quality check, mold trial, and formed a standard process. The iMould system realizes automated processing lines for CNC steel parts, CNC electrodes and EDMs, so as to realize fully automated processing of most molds.



品质控制

Quality Control

高精度检测设备 | HIGH PRECISION TESTING EQUIPMENT

兆威拥有德国蔡司CT、德国蔡司三坐标、WERTH三次元、日本大阪齿轮检测中心、日本大阪齿轮啮合仪、OGP平面测试仪、瑞士热重分析仪(TGA)等多台高精度检测设备，为品质提供了保障。



德国蔡司三坐标
Zeiss CMM (Germany)



日本大阪齿轮检测中心
Osaka Gear Measuring Center (Japan)



日本大阪齿轮啮合仪
Osaka Gear Meshing Device (Japan)



美国OPG影像仪
OPG Projector (United States)



海克斯康影像仪
HEAXGON Projector



德国Mahr圆柱度测量仪
Cylindricity Measuring Machine (Germany)



德国WEITH三次元
WEITH CMM (Germany)



瑞士梅特勒-托利多TGA热重分析仪
METTLER TOLEDO TGA (Switzerland)



RoHS分析仪
RoHS Analyzer

德国蔡司CT | GERMAN ZEISS METROTOM

蔡司METROTOM是基于CT传感器的坐标测量机，其融合X射线计算机断层扫描(CT)及三坐标测量机(CMM)的功能优势。工业CT定位于无损探伤，主要应用于内部缺陷、气孔、裂纹、杂质及三维装配结构等，更重要用于无损几何尺寸测量、色差数模比对、无损内部缺陷及装配结构分析，其权威的可追溯性计量性能、核心的坐标测量机高精度部件、CAA误差补偿、自校准装置及智能测量平台等技术优势。



ZEISS METROTOM is a coordinate measuring machine based on CT sensors, and combines functional advantages of X-ray, computed tomography (CT), and coordinate measuring machine (CMM). Industrial CT is positioned for non-destructive inspection, mainly used for internal defects, pores, cracks, impurities and 3D assembly structures, etc., and more importantly for non-destructive geometric measurement, color difference digital-analog comparison, non-destructive internal defects and assembly structure analysis. It has technical advantages, including its authoritative traceability measurement performance, core high-precision components of coordinate measuring machine, CAA error compensation, self-calibration device, intelligent measurement platform, etc.

KLINGELNBERG 齿轮检测中心 | KLINGELNBERG GEAR MEASURING CENTER

KLINGELNBERG(克林贝格)全自动精密测量中心，用于检查圆柱齿轮齿形、切割齿和剃齿刀、蜗轮蜗杆、滚刀、锥齿轮，以及轴对称工件的尺寸、形状和位置偏差，以及曲线和凸轮廓测量和转子测量。采用四轴联动测量技术，适用于各个形状的测量。全自动技术一次装夹中完成以下所有测量：齿轮测量、坐标点测量、形状和位置测量、粗糙度测量、轮廓测量和光学测量。



KLINGELNBERG is a fully automatic precision measuring center, used to check cylindrical gear, shaved gear and shaving cutter, worm and gear, hob, and bevel gear. Also it can check general dimension, shape, and positional deviation of axially symmetrical workpiece, cam and camshaft measuring and rotor measuring. It adopts four-axis linkage measuring technology, which is suitable for various shape measuring. With fully automatic technology, KLINGELNBERG can complete various measuring tasks, including gear, coordinate point, shape and position, roughness, profile and optical measuring in a single clamping.

品质控制

Quality Control

丹麦B&K PULSE噪音与振动分析系统 | DENMARK B&K PULSE NOISE AND VIBRATION ANALYSIS SYSTEM

PULSE系统是由软件跟硬件两部分组成的噪音及振动的多功能分析仪。可实时、FFT(频谱分析,或者说傅里叶分析)、CPB(三分之一倍频程分析)、Overall(噪音总值)等分析。同时含有数据采集、自动校准、测量、实时多分析、后处理及报告生成。



PULSE Labshop

分析功能: 噪音的声压级总值、固有频率、振动加速度等; 对噪音进行频谱分析、FFT随时间变化的云图显示、噪音总值对时间变化、CPB合成、信号相关等。

Analysis functions: total sound pressure level of noise, natural frequency, vibration acceleration, etc.; Spectrum analysis of noise, cloud image display with FFT over time, total noise versus time, CPB synthesis, signal correlation, etc.




瑞士梅特勒-托利多TGA热重分析仪 | SWITZERLAND METTLER TOLEDO TGA THERMO GRAVIMETRIC ANALYZER

热重分析仪是一种利用热重法检测物质温度与质量变化关系的仪器。在加热过程(塑料800°C、金属粉末1200°C)中有升华、汽化、分解出气体或失去结晶水时,被测的物件质量就会发生变化,这时热重曲线就有所下降。通过分析热重曲线,就可以知道被测物质在多少度时产生变化,并且根据失重量可以计算失去了多少物质,从而得到材料物质的成份。主要用于聚合物(热塑性塑料、热固性树脂、弹性体、粘合剂和复合材料)及金属粉末冶金的材料的测试。



表面粗糙度测试 | SURFACE ROUGHNESS MEASURING MACHINE

德国MAHR表面粗糙度测量系统来检验齿轮外形表面粗糙度,测试结果JIS (JIS B0601-2001,JIS B0601-1994,JIS B0601-1982),VDA,ISO-199以及ANSI。除计算结果外还可以显示组合计算结果和评估轮廓,负载曲线以及振幅分配曲线。



German Mahr surface roughness measuring machine, is used to measure gear surface roughness, result can meet JIS (JIS B0601-2001, JIS B0601-1994, JIS B0601-1982), VDA, ISO-199 and ANSI requirements. Except test result, it can also display combined calculation results and evaluate profile, load curve and amplitude curve.

德国Mahr圆柱度测量仪 | GERMAN MAHR CYLINDRICITY MEASURING MACHINE

MMQ 150 是一款可自动测量形状和位置公差的测量仪器,可在生产或测量室使用,测量精确、针对形位公差进行了优化,可以减少不合格零件的数量。



可测量参数 :
圆度、直线度、平面度(圆形扫描评定)、平行度、锥度、同心度、同轴度、跳动,圆柱度、斜度、垂直度(以圆形扫描面为基准)、角度、扇形区间上的圆度、平面度、径向跳动-区间上的直线度评定。



径向跳动误差:0.0006
径向跳动误差:0.0003
轴向跳动误差:0.0006
圆度误差: 0.0003

Radial runout deviation ($\mu\text{m} + \mu\text{m}/\text{mm}$ measuring height): 0.0006
Radial runout deviation ($\mu\text{m} + \mu\text{m}/\text{mm}$ measuring height): 0.0003
Axial runout deviation ($\mu\text{m} + \mu\text{m}/\text{mm}$ measuring radius): 0.0006
Roundness deviation ($\mu\text{m} + \mu\text{m}/\text{mm}$ measuring radius): 0.0003

品质控制 Quality Control

瑞士梅特勒-库伦法卡尔费休水分仪 | SWITZERLAND METTLER TOLEDO KARL FISCHER TITRATOR

采用I2、SO2、吡啶、无水CH3OH(含水量在0.05%以下)配制试剂,测定出试剂的水当量,在试剂与样品中的水进行反应后,通过计算试剂消耗量而计算出样品中水含量,国际标准化组织把这个方法定为测微量水分国际标准,我们国家也把这个方法定为国家标准测微量水分。


卡尔费休水分测定法,已被很多国际标准,如ISO, ASTM, DIN, BS, 和JIS等公认为准确性最高的方法。

1. 应用范围广泛,可适用多种有机和无机物的水分测定。
2. 可测量的样品含水量:1PPM-5%
3. 可选择使用有隔膜或无隔膜的电解电极。



瑞士梅特勒-差示扫描量热仪 | SWITZERLAND METTLER TOLEDO DIFFERENTIAL SCANNING CALORIMETER

差示扫描量热法DSC一种热分析法。在程序控制温度下,测量材料和参比物的功率差与温度的关系。差示扫描量热仪记录到的曲线称DSC曲线,它以样品吸热或放热的速率,即热流率dH/dt(单位毫焦/秒)为纵坐标,以温度T或时间t为横坐标,可以测量多种热力学和动力学参数,例如比热容、反应热、转变热、相图、反应速率、结晶速率、高聚物结晶度、样品纯度等。该法使用温度范围宽(-175~725°C)、分辨率高、试样用量少。适用于无机物、有机化合物及药物分析。提供物理、化学变化过程中有关的吸热、放热、热熔变化等定量或者定性的信息。



不同材料的熔融峰,峰的大小和在温度轴上的位置明显不同。PP和POM的例子表明,鉴定既取决于熔点,又取决于熔化的焓(压力与体积的乘积,单位是焦耳)



德国徕卡(Leica)金相显微镜 | GERMAN LEICA MICROSCOPE

徕卡Leica DM2700 M 金相显微镜由高质量的徕卡光学元件以及先进的通用白光 LED 照明组成。徕卡 DM2700 M 能够装配先进的配件,例如放大倍数从5x到100x、具有22mm视场、提供平像场和大范围工作距离的 N PLAN 消色差物镜系列。可以对金属材料的金相—金属材料的排布,塑胶材料的洁净度—塑胶材料的颗粒大小及排布进行分析。


Leica DM2700 M microscope combines high-quality Leica optical elements with advanced LED illumination. It is an ideal inspection tool for all kinds of routine inspection tasks in metallography, earth science, forensic investigation, and materials quality control and research. The Leica DM2700 M can be equipped with advanced accessories, e.g. with an N PLAN achromatic objective series with magnifications from 5x to 100x, a field of view of 22 mm, a flattened image field, and large working distances. It can be used to analyze metallography of metal materials—arrangement of metal materials, cleanliness of plastic materials—particle size and arrangement of plastic materials.



轮廓度测试仪 | PROFILE MEASURING INSTRUMENT

齿轮及其外形测量直接驱动C轴的高精度三维矢量扫描传感器保证了精度及效率。全自动检测项: - 直齿齿轮及斜齿圆柱齿轮- 弧齿锥齿轮及准双曲面锥齿轮- 冠轮- 圆柱蜗杆- 锥形圆柱齿轮- 扇形齿轮- 齿轮滚刀- 剃齿刀- 插齿刀- 斜面体齿轮- 同步齿轮可以测量诸如直径、距离、跳动、同心度、平面度等参数。另外其他像圆度、圆柱度、同心度、角度等。

A high precision profile measuring instrument drives a 3D vector scanning sensor on C axis to measure gear and its shape, and ensures product precision and efficiency. This instrument can automatically measure spur gear, helical cylindrical gear, spiral bevel gear and hypoid bevel gear, crown gear, cylindrical worm, conical cylindrical gear, sector gear, gear hob, shaving cutter, gear shaper, beveloid gear and synchronous gear. It can measure parameters including diameter, distance, runout, concentricity and flatness, and also roundness, cylindricity, concentricity and angle.



品质控制

Quality Control

实验室设备 | LABORATORY EQUIPMENT



产品的可靠性及稳定性是评价产品技术水平的综合指标。为了能够分析、评价、验证和提高产品的可靠性，了解总成及零部件在失效情况下而获得可靠数据。兆威建立了驱动模块实验室——拥有多功能震动仪、恒温恒湿箱、冷热冲击试验箱、淋雨实验箱、盐雾试验机、噪音室等多功能实验设备。

Product reliability and stability is a comprehensive indicator to evaluate its technical level. In order to analyze, evaluate, verify and improve product reliability, and get reliable data in failure conditions for assemblies and parts, ZHAOWEI established a drive module laboratory, with multifunctional laboratory equipment including 3D vibration testing device, constant temperature and humidity chamber, thermal shock chamber, rain test chamber, salt spray test chamber and noise test room.



生产实力 Production Capability

深圳市兆威机电股份有限公司引进自动化生产线，严格实施 IATF16949 (CN11/30730.01)、ISO14001 (U006616E0153R3M)、ISO9001:2015 (CN11/30731)、ISO13485 (CN18/4201) 体系标准，采用短线扁平化、注塑与组装自动化的生产模式，完整的PCBA生产线，缩短生产周期，交货快，实现共赢。

ZHAOWEI has designed and installed automatic production lines and strictly implemented IATF16949 (CN11/30730.01), ISO14001 (U006616E0153R3M), ISO9001:2015 (CN11/30731), ISO13485 (CN18/4201) system standards. By adopting production mode of short-term and flat management, automatic injection molding and assembling, complete PCBA production line, ZHAOWEI shortened production cycle and realized fast delivery, can achieve win-win situation.

MES系统 MES System

为了更好对生产现状及品质进行监管,引进了MES生产系统,MES系统可实现注塑工艺的远程监控、注塑工艺、品质监测的管理功能。

In order to better manage production status and monitor product quality, ZHAOWEI introduced MES system. MES system realized remote monitoring of injection molding process and technology, and product quality as well.



粉末冶金生产线 Powder Metallurgy Production Lines

兆威粉末冶金生产线,拥有16台日本月村(YUEH TSUEN)粉末成形机,2条马勒(Mahler)氨氢烧结炉。通过多轴机械臂实现自动分拣、MES生产信息化管理系统逐步的导入打造出一个可靠、全面的制造协同管理生产中心。

ZHAOWEI Powder Metallurgy Production Lines have 16 Japan YUEH TSUEN powder compacting presses and 2 Mahler sintering furnaces. With multi-axis manipulators, we realized automatic product sorting, and with MES system, we can gradually create a reliable and comprehensive collaborative production management center.



注塑零件生产线 Injection Molding Parts Production Lines

兆威零件生产中心拥有住友、FANUC、Sodick等日本进口注塑成型设备200余台。通过模腔压力技术配合机械手实现自动分拣的同时，导入MES生产信息化管理系统，打造出一个可靠、全面的制造协同管理生产中心。

ZHAOWEI Parts Production Center has more than 200 injection molding machines imported from Japan, including Sumitomo, FANUC and Sodick. With cavity pressure technology and manipulators, we realized automatic product sorting, and with MES system, we can gradually create a reliable and comprehensive collaborative production management center.




自动化零部件生产线 Automated Parts Production Lines

兆威所有成型注塑机都配备伺服机械手，提高生产效率的同时，也能提高产品品质的一致性。

- 采用伺服机械手可以实现产品的自动分拣；
- 多功能、多方位工序的自动化。

All injection molding machines of ZHAOWEI are equipped with servo manipulators, which improves production efficiency and quality consistency.

- Servo manipulators can achieve automatic product sorting.
- Had achieved multifunctional and multidirectional process automation.




组装生产线 Assembly Lines

兆威通过对装配生产线的研究,将生产、工业工程技术在生产线中加以运用,从场地节约、流水线设计、布局、管理、日常保养维护到员工单位劳动时间的强度降低等方面对现有生产进行了改善。



自动组装生产线 Automatic Assembly Lines

兆威所有成型注射机设备都配备伺服机械手,提高生产效率及生产及品质的一致性。自动生产线图像识别、机械手和EPSON系统通过图像识别、伺服机器人协作完成整个齿轮箱的组装。



PCBA生产线 PCBA Production Lines

兆威机电拥有完整PCBA生产线，包括西门子SMT贴片线、DIP插件线、分板线、涂覆线，以及日联-X-Ray、FAI自动首件检测仪等对应检测设备确保制造可靠性。



全自动分板线
Fully-automatic Depaneling Line



SMT贴片线
SMT Line



DIP插件线
DIP Line



涂覆线
Coating Line

3.4 mm

产品体系
PRODUCT SERIES

兆威导入传感器与控制器等智能硬件设计、制造。根据客户的需求，我们将微型传动及电子驱动单元整合，可让复杂的机电驱动系统智能化运转。

ZHAOWEI introduced design and production of intelligent hardware like sensors and controllers. According to customer needs, ZHAOWEI integrates micro-drive parts and electronic units and makes complex electromechanical system to operate intelligently.

www.szzhaowei.com

齿轮零部件

Gear Parts

MIM齿轮 | METAL INJECTION MOLDING GEARS



金属镶嵌件 | METAL INSERTS



塑料齿轮 | PLASTIC GEARS



机加工齿轮 | MACHINED GEARS



粉末冶金齿轮 | POWDER METALLURGY GEARS



精密部件 | PRECISION PARTS



标准品

Standard product

兆威致力于为全球客户提供微型驱动解决方案。基于20余年的微型驱动领域经验,实现了电控系统+传动系统+电机系统三位一体的研发体系,其中齿轮箱系列有,行星齿轮箱、直角电机齿轮箱、正传动齿轮箱和零背隙齿轮箱;电机系列有无刷空心杯电机、步进电机、有刷直流电机;电控系统有编码器、电控板等,还可根据客户要求进行定制化规划,实现大批量生产。

ZHAOWEI is dedicated to providing micro-drive solutions to global customers. With over 20 years of experience in the micro drive industry, ZHAOWEI offers integrated R&D capabilities in electronic control systems, transmission systems, and motor systems. The firm's product lines cover gearboxes, motors, and electronics controllers. The gearbox series includes planetary gearboxes, right-angle motor gearboxes, spur gearboxes, and zero-backlash gearboxes. The motor series features brushless coreless motors, stepper motors, and brushed DC motors. The control system includes encoders and control boards. We provide customized solutions tailored to specific client needs, with the capacity for large-scale production.

齿轮箱 | GEARBOX



SMD行星齿轮箱
SMD planetary gearbox



MD行星齿轮箱
MD planetary gearbox



PD行星齿轮箱
PD planetary gearbox



零背隙齿轮箱
Zero backlash gearbox



PL直角电机齿轮箱
PL right-angle gear motor



MC正传动减速箱
MC spur gearbox

电机 | ELECTRIC MACHINERY



MC无刷空心杯电机
MC coreless brushless motor



MP有刷直流电机
MP brushed DC motor



MC步进电机
MC stepper motor



CB-ST编码器
CB-ST encoder



电路板
PCB

电控系统 | ELECTRONIC CONTROL SYSTEM

兆威定制化微型驱动系统解决方案

Zhaowei Customization Micro drive system solution

基于精密、微小、尖端的微型驱动工艺，我们致力为客户定制研发，提供从创意到大批量生产一站式微型驱动系统服务。

Based on precision, miniaturization, and cutting-edge micro drive technology, we are committed to customized research and development for customers, providing one-stop micro drive system services from creativity to mass production.



汽车电子
Automotive Electronics



智慧医疗
Smart healthcare



智能家居
Smart Home



消费电子
Consumer electronics



机器人
Robot



工业自动化
Industrial Automation

汽车驱动系统

Automotive Drive



汽车电动冰箱执行器 | AUTOMOBILE ELECTRIC REFRIGERATOR ACTUATOR



产品说明:

兆威机电采用蜗杆斜齿形式，通过电机模组与输出轴结合，实现车载冰箱的直线往复开合运动，且具有自锁功能，确保冰箱在坡道等倾斜状态下也能保持稳定。

Product Description:

ZHAOWEI employs a worm and helical gear structure, seamlessly integrating the motor module with the output shaft to precisely drive the linear reciprocating opening and closing motion of in-vehicle refrigerators. This design incorporates a self-locking feature, ensuring the refrigerator remains securely positioned even on inclined surfaces.

汽车屏类执行器解决方案 | SOLUTION FOR AUTOMOTIVE SCREEN ACTUATORS




产品说明:

兆威是汽车屏类执行器方案专家，拥有中控屏翻转、旋转、滑动、两度自由、遮阳屏翻转、后排扶手屏翻转等屏幕定制化方案经验，赋能车企智能化场景应用。

Product Description:

As an expert in automotive display actuator solutions, ZHAOWEI provides customized designs, including central control screen flipping, rotating, sliding, and dual-degree-of-freedom movement, sunshade screen flipping, rear armrest screen flipping. These solutions empower automotive manufacturers with intelligent, scenario-based applications.

尾门电机模组 | TAILGATE MOTOR MODULE



产品说明:

兆威汽车尾门电机模组，通过电机驱动行星传动减速，带动输出花键进行旋转运动为螺杆输出扭矩，推动尾门撑杆做升降运动。该产品可在有限空间内输出较大支撑力矩，广泛适用于SUV、轿车等汽车尾门升降场景。

Product Description:

The Zhaowei car tailgate motor module drives planetary transmission deceleration through the motor, driving the output spline to rotate and output torque as a screw, and pushing the tailgate strut to move up and down. This product can output a large support torque in a limited space and is widely used in scenarios such as SUV and sedan tailgate lifting.

电子驻车执行器MGU | ELECTRONIC PARKING ACTUATOR MGU





产品说明:

兆威电子驻车MGU，通过电机，输出转轴传递动力至卡钳中的螺杆螺套组件，螺杆螺套组件将转矩转变为线性动力来推动活塞，从而夹紧制动盘，实现驻车。

Product Description:

The Zhaowei Electronic Parking MGU transmits power to the screw sleeve assembly in the caliper through the output shaft of the motor. The screw sleeve assembly converts torque into linear power to push the piston, thereby clamping the brake disc and achieving parking.

隐藏门把手执行器 | FLUSH DOOR HANDLE ACTUATOR




产品说明:

兆威隐藏门把手执行器采用结构紧凑的微型驱动设计，能够在兼具小体积的同时，输出较大扭矩，实现车辆门把手伸缩功能。

Product Description:

The flush door handle actuator employs a compact micro-drive design, delivering high torque output despite its small size. This enables smooth sliding, popping, and retracting actions, ensuring reliable performance and maintaining the sleek aesthetics of the vehicle's flush door handles.

充电桩锁止执行器 | CHARGING GUN LOCK ACTUATOR





产品说明：

公司新能源充电桩锁止执行器，通过调整充电桩锁止齿轮箱模数和材料对环境的适应性效能，并通过巧妙的驱动结构，使充电桩正向运动时充电插头稳定保持在插座或固定座的扣位内，实现锁定功能。

Product Description:

The company's new energy charging gun locking actuator adjusts the adaptability of the charging gun locking gearbox module and material to the environment, and through a clever driving structure, stabilizes the charging plug in the socket or fixed seat when the charging gun moves forward, achieving the locking function.

汽车尾翼执行器 | ACTIVE REAR SPOILER LIFT ACTUATOR



产品说明：

兆威尾翼升降执行器，利用空间紧凑的蜗轮蜗杆传动，实现汽车尾翼不同挡位的升降调节，实现自锁及多级悬停。



Product Description:

The rear spoiler lift actuator utilizes a compact worm and gear transmission system to enable multi-level adjustment of the rear spoiler. It provides self-locking functionality and supports multiple hover positions for enhanced aerodynamic performance and vehicle stability.

两轮车ABS | TWO WHEELED VEHICLE ABS



热管理阀门 | THERMAL MANAGEMENT ACTUATOR



产品说明:

兆威两轮刹车ABS, 主要用于摩托车刹车系统之上, 产品通过驱动马达带动齿轮箱转动, 具有运行稳定、寿命长的特点。

Product Description:

Zhaowei two wheel brake ABS is mainly used in motorcycle brake systems. The product is driven by a motor to rotate the gearbox, and has the characteristics of stable operation and long service life.

产品说明:

兆威热管理执行器由直流无刷电机+齿轮传动模组组成, 通过电机驱动水阀, 调节各管路流量分配, 使电机电池处于最适合的温度环境, 实现热量有效利用。

Product Description:

The thermal management actuator consists of a DC brushless motor and a gear transmission module. By driving water valves, it adjusts the flow distribution across different pipelines, ensuring the optimal temperature environment for the motor and battery. This facilitates effective heat utilization and improved system efficiency.

工业自动化

Industrial Equipment Drive

兆威机电深度洞察工业化升级的驱动应用和客户需求，基于多年技术积淀和匠心制造，以品质为根本，开发出适合市场和客户需求的产品，包括滚筒电机、阀门执行器、精密设备、通讯设备等平台化产品。

兆威秉承精益求精理念，不断挑战驱动技术应用，完成高品质、高性能微型驱动生产，赋能工业化蓬勃发展。

ZHAOWEI deeply understands the evolving demands of industrial upgrades and drive applications. Leveraging years of technical expertise and advanced manufacturing, we prioritize quality as the foundation for developing products tailored to market and customer needs. Our offerings include platform-based solutions such as drum motors, valve actuators, drive systems for precision equipment and communication devices.

Adhering to a philosophy of continuous improvement, ZHAOWEI consistently pushes the boundaries of drive technology applications, delivering high-quality, high-performance micro-drive solutions that empower industrial advancement.



工业风/水阀门 | INDUSTRIAL AIR / WATER VALVE




产品说明：

兆威风/水阀执行器集中电控、齿轮箱传动、驱动电机一体化设计，具备一定自锁力，具有体积小、耐高温、负载能力大、噪音小、成本低、寿命长等特点。

Product Description:

The Zhaowei wind/water valve actuator is designed with centralized electronic control, gearbox transmission, and integrated drive motor, which has a certain self-locking force. It has the characteristics of small size, high temperature resistance, large load capacity, low noise, low cost, and long service life.

安防监控智能云台驱动系统 | INTELLIGENT PTZ DRIVE SYSTEM FOR SECURITY MONITORING




产品说明：

兆威安防监控智能云台驱动系统，采用兆威自研齿轮箱，实现安防镜头旋转、仰俯等动作，具有定位精度高、噪音低、寿命长等特点。

Product Description:

The Zhaowei security monitoring intelligent pan tilt drive system is selected from Zhaowei's self-developed gearbox, which realizes the rotation, tilt and other actions of the security lens. It has the characteristics of high positioning accuracy, low noise, and long service life.

滚筒电机解决方案 | DRUM MOTOR SOLUTION





产品说明：

兆威推出全新滚筒电机平台，采用均为自研高性能齿轮箱、电机和控制器，为客户带来稳定高效的滚筒电机解决方案。该方案拥有多种直径、长度、功率组合，满足客户定制化搭配。

Product Description:

The newly launched drum motor platform incorporates ZHAOWEI's self-developed high-performance gearboxes, motors, and controllers. With various diameter, length, and power combinations, it delivers stable, efficient, and customizable solutions for client needs.

RCU模组 | RCU MODULE



产品说明：

兆威为客户提供的RCU模组中涵盖硬件及驱动模块设计的整套解决方案，配合客户的软件系统，可用来远程调节基站天线辐射信号的下倾角，进而调整网络覆盖位置及范围等。

Product Description:

ZHAOWEI's RCU module includes a comprehensive design for hardware and drive modules, integrated with client software systems. It allows remote adjustment of base station antenna tilt angles, optimizing network coverage and range.

智慧医疗

Medical Micro Drive Systems


随着医疗技术发展，微型驱动系统在医疗领域应用越发广泛，例如医疗注射泵，外科手术器械、医疗植入设备、康复设备等。其中，医疗手术机器人，凭借精细操作，备受各大医疗器械公司重视。

以上产品对微型驱动系统性能要求精密，兆威拥有多年医疗微型驱动系统研发制造经验，建有自动化无尘车间，配合MES生产管理体系，提高医疗驱动产品生产效率，致力为全球医疗器械客户提供微型驱动优质解决方案。

The evolution of medical technology has expanded the applications of micro drive systems in areas such as medical infusion pumps, surgical instruments, medical implants, rehabilitation devices. ZHAOWEI specializes in high-precision micro drive systems for the medical field. Our automated cleanrooms and MES production management systems enhance efficiency and ensure superior solutions for global medical device clients.



钻骨电机 | DRILLING MOTOR

**产品说明:**

兆威钻骨电机选用高频无刷电机保证切割钻头的高速旋转，同时其具有低噪的优点，在钻头两侧设计有同步清洗切削碎屑清理液喷射的管道，通过独立于钻头驱动结构外的壳体边缘喷出，实现对创口的及时清洗。

Product Description:

The Zhaowei bone drilling motor uses a high-frequency brushless motor to ensure the high-speed rotation of the cutting drill bit, and it has the advantage of low noise. There are pipes designed on both sides of the drill bit for synchronously cleaning cutting debris cleaning fluid, which is sprayed out through the edge of the shell independent of the drill bit driving structure to achieve timely cleaning of the wound.


骨科手术创面清洗泵驱动系统 | DRIVE SOLUTION FOR ORTHOPEDIC SURGICAL WOUND IRRIGATION PUMP

**产品说明:**

兆威骨科手术创面清洗泵系统，用于骨科手术中洗流里调节。本产品通过直流电机+面齿轮传动对流量进行控制，多挡位调节功能，可根据手术要求进行合理选择，控制流量大小给出。

Product Description:

Zhaowei Orthopedic Surgical Wound Cleaning Pump System is used for adjusting the washing flow during orthopedic surgery. This product controls the flow rate through a DC motor and face gear transmission, with multi gear adjustment function. It can be selected reasonably according to surgical requirements to control the flow rate.

电动吻合器驱动系统 | ELECTRIC STAPLER DRIVE SYSTEM

产品说明：

兆威微创电动吻合器驱动系统，采用电机带动行星齿轮箱传动模式，驱动皮肤钉合器的前后移动，从而实现缝合功能，具备力矩大、结构紧凑、噪音低等特点。

Product Description:

The Zhaowei Minimally Invasive Electric Stapler Drive System adopts a motor driven planetary gearbox transmission mode to drive the forward and backward movement of the skin stapler, thereby achieving the suturing function. It has the characteristics of high torque, compact structure, and low noise.

胰岛素泵驱动系统 | INSULIN PUMP DRIVE SYSTEM

产品说明：

兆威胰岛素注射泵，采用步进电机搭配平行传动模式，由螺母丝杆结构推动注射活塞，根据人体所需剂量将胰岛素注入到患者皮下，达到控制胰岛素注射量的目的，具有运行平稳、噪音低等特点，适用于绝大多数胰岛素注射设备。

Product Description:

The Zhaowei insulin injection pump adopts a stepper motor combined with a parallel transmission mode. The injection piston is driven by a nut screw structure, and insulin is injected subcutaneously into the patient according to the required dosage of the human body, achieving the goal of controlling insulin injection volume. It has the characteristics of smooth operation and low noise, and is suitable for the vast majority of insulin injection equipment.

智能家居

Smart Home

在智能化的时代下，家居已经智能与省心结合，为智能家居带来全新体验。兆威秉承“致力微型驱动领域进步，共创智能美好生活”的使命愿景，以微型驱动赋能家居办公、厨卫家电、母婴用品、骑行装备等场景，协同全球客户，共创智能美好生活。

In the era of intelligence, home furnishings have combined intelligence and ease of mind, bringing a new experience to smart homes. Zhaowei adheres to the mission vision of "dedicating itself to the advancement of micro drivers and creating an intelligent and beautiful life together", empowering intelligent cleaning, kitchen and bathroom appliances, maternal and child products, cycling equipment and other scenarios with micro drivers, collaborating with global customers to create an intelligent and beautiful life.



洗地机驱动解决方案 | SOLUTION FOR FLOOR SCRUBBER DRIVER




产品说明：

兆威洗地机驱动模组由直流电机和平行轴传动齿轮机构组成，控制清扫信号输入后，电机驱动主动齿轮与从动齿轮的啮合，传递运动和动力组，带动洗地机的滚筒进行清扫，实现高低速不同清洁模式。

Product Description:

The Zhaowei floor scrubber drive module consists of a DC motor and a parallel axis transmission gear mechanism. After controlling the cleaning signal input, the motor drives the meshing of the driving gear and the driven gear, transmitting motion and power to drive the drum of the floor scrubber for cleaning, achieving different cleaning modes of high and low speed.

扫地机驱动解决方案 | VACUUM CLEANER DRIVE SOLUTION


**产品说明：**

兆威扫地机驱动解决方案，通过传动系统创新设计，和防发丝缠绕等结构优化，为客户带来扫地机全套驱动解决方案，其中包括主刷、边刷、拖地/洗地、前后驱动等多种电机，具有噪音低、扭矩大等特点。

Product Description:

The robot vacuum drive solution features innovative transmission designs and optimized anti-hair entanglement structures, providing a comprehensive drive system for vacuum robots. This includes components for the main brush, side brush, mopping, scrubbing, and front/rear-wheel drives, characterized by low noise, high torque, and enhanced reliability.

电视机摄像头驱动系统 | DRIVE SYSTEMS FOR TV POP-UP CAMERA

**产品说明：**

电视机摄像头驱动系统，采用步进电机+行星齿轮箱结构，通过双导杆输出，保证运行稳定不卡顿，且传动效率高、噪音低。升降式摄像头具有可隐藏，占用外部空间小等优点，不仅提高了屏占比，也使产品更美观。

Product Description:

ZHAOWEI TV pop-up camera drive system adopts stepping motor and planetary gearbox structure, and double guide bars output to ensure stable operation without jamming, high transmission efficiency and low noise. This pop-up camera design has advantages of being hidden and occupying less external space, which improves screen ratio, also makes the television more beautiful.

智能家居门锁控制系统 | DRIVE SYSTEMS FOR DOOR LOCK



产品说明:

智能门锁驱动系统采用多级平行齿轮箱传动，通过齿轮箱传动拉动锁芯，能有效的控制锁芯的开锁、闭锁功能。这种设计使得锁芯可控、可靠性高、寿命长，开锁的速度快。同时齿轮箱带自锁功能，电池断电时可通过手动开关锁。

Product Description:

ZHAOWEI intelligent door lock drive system adopts multi-stage parallel transmission gearbox, can pull and push the lock cylinder to effectively control locking and unlocking functions of door lock. This design makes the lock cylinder controllable with high reliability, long service life and fast feedback. The gearbox has self-locking function, switch can be manual controlled when battery is powered off.

智能电动窗帘驱动系统 | DRIVE SYSTEMS FOR ELECTRIC CURTAIN




产品说明:

该窗帘传动模组采用行星齿轮箱多级传动，在满足力矩同时部分齿轮采用塑胶人字齿形设计，解决了管状电机驱动系统噪音大的问题，同时寿命也大大提高。

Product Description:

ZHAOWEI electric curtain drive system adopts a multi-stage planetary transmission gearbox. This design partially adopts plastic herringbone tooth structure, can meet torque requirement, solve problem of high noise of tubular motor drive system, and greatly improve service life.

冰箱门开合驱动系统 | DRIVE SYSTEMS FOR FRIDGE DOOR OPENING AND CLOSING




产品说明：

该系统结合距离感应器(红外线传感器等)可解决现有冰箱开关门不方便的弊端,通过网络控制、开关控制、语音控制控制驱动装置向门体传递驱动力可实现冰箱门稳定开合。

Product Description:

Combined with distance sensors (e.g. infrared sensor), the drive system transmits driving force to the fridge door, realizes stable fridge door opening and closing, and can be controlled through internet control component, switch control component, and voice control component.

智能马桶翻盖驱动系统 | DRIVE SYSTEMS FOR SMART TOILET LID



产品说明：

为解决双个翻盖面板的困难及翻盖时间长及力矩寿命的问题,我们研发出阻尼减速驱动系统机构,采用斜齿及行星驱动系统双重结构,能轻松翻起马桶的面盖。

Product Description:

To solve the difficulty of flipping double toilet lids and long time flipping process, and increase torque and lifetime, ZHAOWEI developed a damping speed reduction drive mechanism. The system adopts dual structure of helical gears and planetary drive mechanism, to achieve toilet lid stable flipping-up function.

儿童安全座椅 | CHILD SAFETY SEAT ACTUATORS



产品说明:

齿轮箱通过平行传动，实现减速增矩的作用，最终带动蜗杆与客户处斜齿轮配合，带动儿童座椅实现旋转和倾角运行。

Product Description:

Through parallel transmission, ZHAOWEI gearboxes achieve torque multiplication and speed reduction, driving worm gears to interact with client-specific helical gears. This enables smooth rotation and angle adjustment for child safety seats.

消费电子

Consumer Electronics

如今，“轻、薄、快”几乎已经成为消费电子产品的代名词，而兆威在创立之初便确立了“精密 微小 超薄”的技术路线，在<2014年成功研发出Φ3.4mm行星减速箱，多年来兆威不断追求技术创新，制造工艺突破，愿协同全球客户，赋能虚拟现实、3C电子、美容养生等消费电子行业进步。

Nowadays, "light, thin, and fast" has almost become synonymous with consumer electronics products. At the beginning of its establishment, Zhaowei established the technical route of "precision, micro, and ultra-thin". In 2014, it successfully developed a planetary gearbox with a diameter of 3.4mm. For many years, Zhaowei has been continuously pursuing technological innovation, making breakthroughs in manufacturing processes, and is willing to collaborate with global customers to empower the progress of consumer electronics industries such as virtual reality, 3C electronics, and beauty and health.



IPD瞳距调节模组 | IPD PUPIL DISTANCE ADJUSTMENT MODULE





产品说明:

兆威瞳距调节装置是一种调节智能穿戴设备两个镜片之间的间距，以与使用者瞳距相适配的驱动装置，主要应用于VR头盔、VR眼镜等设备。本产品通过先进工艺和精巧设计，简化组装工艺、提高传递效率和调节精度，减少传动噪音，在降本增效的同时，还能更好保证使用者获得较佳观看效果。

Product Description:

The Zhaowei Pupil Distance Adjustment Device is a driving device that adjusts the distance between two lenses of smart wearable devices to match the distance between the user's pupils. It is mainly used in VR helmets, VR glasses, and other devices. This product simplifies the assembly process, improves transmission efficiency and adjustment accuracy, reduces transmission noise through advanced technology and exquisite design. While reducing costs and increasing efficiency, it can also better ensure that users obtain better viewing effects.

手机摄像头升降驱动系统 | DRIVE SYSTEMS FOR POP-UP PHONE CAMERA



产品说明:

采用步进电机+行星减速器+丝杆设计成的驱动系统，实现了有限体积(厚度4.6mm)内的摄像头稳定低噪升降，解决了全面屏前置摄像头的安置问题。

Product Description:

This drive system consists of stepper motor, planetary reducer and lead screw, it realizes stable lifting of phone front camera with low noise in a limited space (thickness 4.6mm), and solves placement of full-screen phone front camera.

电动云台驱动系统 | DRIVE SYSTEMS FOR MOTORIZED PAN & TILT HEAD



**产品说明:**

采用永磁直流电机和斜齿轮传动结构，解决了电动云台抖动和噪音问题，提高了产品稳定性及使用寿命。

Product Description:

ZHAOWEI motorized pan & tilt head drive system adopts permanent magnet DC motor and helical gear transmission structure, solves jitter and noise problems, and improves product stability and service life.

按摩器驱动系统 | DRIVE SYSTEMS FOR MASSAGER

**产品说明:**

通过低噪音直流无刷马达和高精密蜗轮蜗杆，平行直齿轮传动模组作用力输出，四轴输出力作用于人体头部，肩部，背部位按摩实现低噪音仿生人手按，揉，压等动作，使用寿命长。

Product Description:

This system adopts a drive module with a low noise brushless DC motor, high precision worm, gear, and parallel spur gear pairs, to drive output shafts to work on four massage balls and simulates manual pressing and kneading on the head, shoulder and back, and has a long service life.

智能学习机俯仰调节模组 | SMART LEARNING DEVICE TILT ADJUSTMENT MODULE



产品说明：

兆威智能学习机俯仰调节模组，将马达通电后通过平行传动减速增力，带动丝杆转动，输出螺母上下移动，输出螺母和输入支架连接，带动翻转齿轮箱运动，同时带动摄像头组件旋转。

Product Description:

The pitch adjustment module of the Zhaowei intelligent learning machine, after the motor is powered on, reduces the speed and increases the force through parallel transmission, drives the screw to rotate, and the output nut moves up and down. The output nut is connected to the input bracket, which drives the flipping gearbox to move and also drives the camera component to rotate.

学习机摄像头升降驱动系统 | DRIVE SYSTEMS FOR LEARNING LAPTOP POP-UP CAMERA




产品说明：

兆威优化了学习机外置摄像头方案，将摄像头模块隐藏到学习机内部，从而实现产品一体化；学习机升降摄像头的应用，用户在使用的过程中摄像头模组可以向下拍摄课本内容，实现线上线下互动等场景。提升学生用户体验的同时，也提升了产品科技感。

Product Description:

ZHAOWEI optimized learning laptop external camera solution by hiding the camera module inside the learning laptop, and realized product integration. With pop-up camera application for learning laptop, the camera module can tilt down and shoot textbook content on the desk during the process, and realizes online and offline interaction and other scenarios. This application enhances student experience, also enhances product technology.

笔记本隐藏摄像头驱动系统 | LAPTOP KEYBOARD HIDDEN CAMERA LIFT DRIVE SYSTEM



产品说明：

通过4mm金属行星齿轮箱结合步进电机、丝杆、滑块，来实现笔记本键盘上类似键盘的摄像头按钮升降机构的智能升、降和稳定性。

Product Description:

The hidden camera lift drive system for laptop keyboards incorporates a 4mm-diameter metal planetary gearbox, a stepper motor, a screw, and a sliding block. This system allows for intelligent, stable elevation of the camera, resembling a keyboard key, for seamless integration and enhanced usability.

视频会议驱动系统 | DRIVE SYSTEMS FOR VIDEO CONFERENCE EQUIPMENT




产品说明：

视频会议系统驱动系统的主要问题是回程差。通过对整个驱动系统的结构及设计进行优化，将驱动系统的回程差控制在小弧度以内，实现产品的低噪音。

Product Description:

Main problem of drive system for video conference equipment is the backlash. ZHAOWEI optimizes structural design of the entire drive system and controlled backlash within a small arc, achieves low noise and precise angle adjustment.

脚部按摩器驱动系统 | DRIVE SYSTEMS FOR FOOT MASSAGER



产品说明：

洗脚盆上脚部按摩器驱动系统通过蜗轮蜗杆和平行齿轮箱的作用力使得用户在使用洗脚盆按摩器具时，按摩球头的角度可以自适应用户的需求而进行调节，增大了适用范围。

Product Description:

The foot massager drive system in a foot spa employs a worm and gear mechanism combined with a parallel gearbox. It enables the massage ball heads to adaptively adjust their angles to meet user needs, expanding the range of use and enhancing the overall massage experience.

健身器材驱动系统 | DRIVE SYSTEMS FOR FITNESS EQUIPMENT




产品说明：

通过优化调整跑步机踏板调节齿轮箱结构结合无刷电机，智能调整跑步机踏板角度，实现根据运动强度需求改变跑步机踏板的运动轨迹。

Product Description:

ZHAOWEI optimizes treadmill pedal angle adjusting gearbox structure by cooperating with the brushless motor to realize intelligent treadmill angle adjustment according to exercise intensity.

儿童抒腹仪驱动系统 | DRIVE SYSTEMS FOR CHILDREN ABDOMINAL MASSAGER



产品说明：

通过低噪音直流无刷马达，高精密平行轴齿轮和内齿传动齿轮模组作用，输出旋转运动，通过发热砭石滚动作用于少年儿童腹部，促进儿童肠胃消化，产品使用寿命长。

Product Description:

This system adopts a low noise brushless DC motor and high precision parallel shaft gears, through the internal gear transmission method, to rotate and heat bianstone massage balls that work on children's abdomen. The abdominal massager can promote digestion and has a long service life.

24mm按摩器驱动系统 | DRIVE SYSTEMS FOR MASSAGER (24MM)




产品说明：

通过低噪音直流有刷马达或无刷马达和高精密斜齿轮，直齿轮传动模组作用力输出，施加圆周力于人体颈部按摩，仿生人手按，揉，压等动作，提高产品使用寿命。

Product Description:

This system adopts a low noise brushed DC motor (or brushless DC motor), high precision helical gears, and parallel gears, to apply circular force through massage ball on the neck to simulate manual pressing and kneading, and has a long service life.

美容仪驱动系统 | DRIVE SYSTEMS FOR SKINCARE DEVICE

**产品说明:**

通过低噪音直流有刷马达和高精密平行轴斜齿轮传动，输出旋转运动及振动，作用于人面部进行护理美容，使用寿命长。

Product Description:

This drive system adopts a low noise brushed DC motor and high precision parallel shafted helical gears, and drives the device to rotate and vibrate, and work on face to achieve cosmetic results. It has a long service life.

机器人

Robot


机器人产业作为当代科技进步与经济结构转型的重要交汇点，从工业生产、物流运输、医疗手术、深海作业、高空无人机、生活服务、智能制造等场景，几乎都有机器人的身影。

兆威始终关注机器人前沿技术，从微型驱动领域出发，致力帮助机器人实现应用落地。兆威基于对精密减速箱、高性能电机、电控系统的产品组合，适用于机器人头部、关节、手指等运动执行等应用，具有精度高、尺寸小、重量轻等特点。

Robotics is a key intersection of technological advancement and economic transformation, with applications spanning industrial production, logistics and transportation, medical surgery, deep-sea exploration, aerial drones, smart living, intelligent manufacturing. ZHAOWEI focuses on cutting-edge robotic technologies, offering micro drive solutions for robot heads, joints, fingers. Our products are known for high precision, compact size, and lightweight design.



仿生机器人灵巧手 | BIONIC ROBOTIC DEXTEROUS HAND



产品说明：

兆威仿生机器人灵巧手，集结构、软硬件系统研发于一体。主要应用于机器人领域，可与各种柔性机器人配合使用，具有多自由度和高功率密度的特点，可完成复杂灵巧的抓握动作。

Product Description:

The ZHAOWEI bionic robotic hand integrates structural design with software and hardware development. It features high power density and multi-degree freedom, enabling complex and dexterous grasping actions in robotic applications.

机器人关节驱动系统 | DRIVE SYSTEMS FOR ROBOT JOINT



产品说明：

该系统多为动力类舵机，对减速器的寿命要求高对噪音更敏感。其设计重心放在齿轮参数优化，同时在减速器内部增加离合机构，当机器跌倒减速器受到外接冲击时，齿轮能得到保护，实现小空间大传动比的特性，能完成传动轴六自由度的转换。

Product Description:

This system is mostly a servomotor, which has high requirements for service life of the reducer and is more sensitive to noise. The design focuses on gear parameters optimization, and installs a clutch mechanism on the reducer, when the machine falls and the reducer is subjected to external impact, it can protect gears. This system achieves a large reduction ratio in small space, and the output shaft can move freely in six directions.

标准齿轮箱系列

STANDARD GEARBOXES

兆威为客户提供行星齿轮箱、直角电机齿轮箱、正传动齿轮箱，以及零背隙齿轮箱四种选择，每一款都有合适的使用场景。产品尺寸覆盖3.4mm至42mm直径范围，减速比从3.9到1526。其中零背隙齿轮箱，空载平均空回<1°，能够更好的满足一些高精尖行业应用。

ZHAOWEI offers planetary gearboxes, right-angle gear motors, spur gearboxes, and zero-backlash gearboxes, each tailored to specific applications. Product dimensions range from 3.4mm to 42mm in diameter, with reduction ratios from 3.9 to 1526. And the zero-backlash gearbox, with an average no-load backlash of less than 1°, better meets the needs of high-precision industries.



SMD行星齿轮箱
SMD planetary gearbox



MD行星齿轮箱
MD planetary gearbox



PD行星齿轮箱
PD planetary gearbox



零背隙齿轮箱
Zero backlash gearbox



PL直角电机齿轮箱
PL right-angle gear motor



MC正传动减速箱
MC spur gearbox

SMD行星齿轮箱

SMD planetary gearbox


SMD行星齿轮箱是兆威专门开发的高性能产品，能够在小体积下输出更大扭矩，具有噪音低、间隙小，适合用于传输高扭矩和高转速的应用场景。此外，我们还可搭配无刷、有刷、步进电机等高性能产品，具有模块化组合功能。

Specially developed for high-performance applications, this compact gearbox delivers high torque with low noise and minimal backlash, making it ideal for high-speed, high-torque scenarios. It is compatible with brushless, brushed, and stepper motors, offering modular combinations.



SMD004004

Φ4mm 行星齿轮箱



技术数据

齿轮箱级数	1	2	3	4
连续输出转矩 (Max)	Nm	0.001	0.002	0.006
瞬间容许力矩(Max)	Nm	0.002	0.003	0.008
减速比	/	4.8	23.0	110.6
外直径	mm	4	4	4
齿轮箱长度L1	mm	7.7	9.3	10.9
最大效率	%	87	76	70
建议温度范围	°C	-40~+80	-40~+80	-40~+80
齿轮箱重量 (Max)	G	1	1.2	1.3
最大传输功率 (连续)	W	0.15	0.17	0.12
最大传输功率 (瞬时)	W	0.2	0.21	0.15
空载平均空回	°	5	5	5
最大轴向载荷 (动态)	N	5	5	5
最大径向载荷 (离法兰4mm处)	N	3	3	4
输出端轴承		滚珠轴承	滚珠轴承	滚珠轴承
轴向间隙	mm	0~0.1	0~0.1	0~0.1

*注：以上数据不包含电机，减速箱和电机整体出售，具体参数可根据客户要求定制

模块化组合


组合产品	型号	级数			
		1	2	3	4
直流电机	0408 φ4石墨电刷	15.8	17.4	19.0	20.6
	0412 φ4石墨电刷	20.0	21.6	23.2	24.8
无刷电机	MC0409 φ4mm 空心杯无刷电机	16.2	17.8	19.4	21.0
编码器	/			磁编	

典型应用产品数据

型号	额定电压 (V)	空载数据		负载数据		总长 (mm)	齿轮箱额定 容许力矩 (NM)	齿轮箱瞬间 容许力矩 (NM)	减速比	减速箱长 L1(mm)
		空载转速(rpm)	空载电流(mA max)	负载转速(rpm)	负载电流(mA Max)					
ZWSMD004004-4.8-X	5	9375	140	6250	180	0.0002	16.2	0.001	0.002	4.8
ZWSMD004004-23-X	5	1957	140	1304	180	0.0003	17.8	0.002	0.003	23.0
ZWSMD004004-111-X	5	407	140	271	180	0.0015	19.4	0.006	0.008	110.6
ZWSMD004004-531-X	5	85	140	57	180	0.0069	21.0	0.015	0.02	530.8

*以上规格数据仅供参考，如有修改恕不另行通知，下单前请找客户询问。


3.4
mm
M
Metal 五金

MD003003

齿轮箱规格 Gearbox Specifications

外径	Outer diameter	3.4mm	轴承	Bearing	含油轴承 oil-impregnated bearings
材质	Material	五金 Metal	轴向窜动	Axial Play	≤0.3mm
旋转方向	Direction of rotation	cw & ccw	输出轴径向负载	Radial Load at Output Shaft	≤0.3N
齿轮箱回程差	Backlash	≤3°	工作温度	Operating temperature range	-20 ~ +85°C


齿轮级数 Gearbox Stages	1	2	3	4
减速比 Reduction ratio	5	25	125	625
最大容许扭力(gf.cm) Max rated torque of gearbox (gf.cm)	50	50	50	50
瞬间容许力矩(gf.cm) Max. intermittent torque (gf.cm)	150	150	150	150
齿轮箱效率(%) Gearbox efficiency (%)	85	73	65	58
长度(mm) Gearbox length L1 (mm)	6	7.5	9	10.5

4.3
mm
M
Metal 五金

MD004004

齿轮箱规格 Gearbox Specifications


外径	Outer diameter	4.3mm	轴承	Bearing	含油轴承 oil-impregnated bearings
材质	Material	五金 Metal	轴向窜动	Axial Play	≤0.3mm
旋转方向	Direction of rotation	cw & ccw	输出轴径向负载	Radial Load at Output Shaft	≤0.3N
齿轮箱回程差	Backlash	≤3°	工作温度	Operating temperature range	-20 ~ +85°C

齿轮级数 Gearbox Stages	1	2	3	4
减速比 Reduction ratio	6	36	216	1296
最大容许扭力(gf.cm) Max rated torque of gearbox (gf.cm)	70	70	70	70
瞬间容许力矩(gf.cm) Max. intermittent torque (gf.cm)	200	200	200	200
齿轮箱效率(%) Gearbox efficiency (%)	85	73	65	58
长度(mm) Gearbox length L1 (mm)	6.18	7.67	9.17	10.72

技术插图 | Technical Drawing

马达规格参数 Motor Specifications

马达	Motor type	步进电机 Stepper motor	输入速度	Input speed	≤1000rpm
电压	Voltage	3V	负载电流	Load current	50mA max
型号 Model	Speed at 2400pps 2400pps频率转速 rpm	Max Rated Torque 额定容许力矩 gf.cm	Max. Intermittent Torque 瞬间容许力矩 gf.cm	Reduction Ratio 减速比	Gearbox Length 减速箱长 L1 mm
MD003003-5	1440.0	50	150	5	6.0
MD003003-25	288.0	50	150	25	7.5
MD003003-125	57.6	50	150	125	9.0
MD003003-625	11.5	50	150	625	10.5
					10.75
					12.25
					13.75
					15.25

注:可根据客户要求定制 Specifications can be customized per customer requirements.

技术插图 | Technical Drawing

马达规格参数 Motor Specifications

马达	Motor type	步进电机 Stepper motor	输入速度	Input speed	≤1000rpm
电压	Voltage	3V	负载电流	Load current	50mA max
型号 Model	Speed at 2000pps 2000pps频率转速 rpm	Max Rated Torque 额定容许力矩 gf.cm	Max. Intermittent Torque 瞬间容许力矩 gf.cm	Reduction Ratio 减速比	Gearbox Length 减速箱长 L1 mm
MD004004-6	1000.0	140	400	6	6.18
MD004004-36	166.6	140	400	36	7.67
MD004004-216	27.7	140	400	216	9.17
MD004004-1296	4.6	140	400	1296	10.72
					11.78
					13.27
					14.77
					16.32

注:可根据客户要求定制 Specifications can be customized per customer requirements.


38
mm
Metal
五金

MD038038

齿轮箱规格 Gearbox Specifications

外径 Outer diameter	38mm	轴承 Bearing	滚动轴承 Rolling bearing
材质 Material	五金 Metal	轴向窜动 Axial Play	≤0.1mm
旋转方向 Direction of rotation	cw & ccw	输出轴径向负载 Radial Load at Output Shaft	≤300N
齿轮箱回程差 Backlash	≤2° 可定制 Customizable	工作温度 Operating temperature range	-20 ~ +100°C
齿轮级数 Gearbox Stages		1	2
减速比 Reduction ratio	4 / 6	16 / 25 / 39	64 / 100 / 156 / 244
最大容许扭力(gf.cm) Max rated torque of gearbox (gf.cm)	80000	80000	80000
瞬间容许力矩(gf.cm) Max. intermittent torque (gf.cm)	240000	240000	240000
齿轮箱效率(%) Gearbox efficiency (%)	90	85	80
长度(mm) Gearbox length L1 (mm)	30.7	43.7	56.7
		3	4
减速比 Reduction ratio	256 / 400 / 625 / 977 / 1526		

技术插图 | Technical Drawing



马达规格参数 Motor Specifications

马达(可选择) Motor type (optional)	直流有刷电机、直流无刷电机、步进电机 Brushed DC motor, Brushless DC motor, Stepper motor	输入速度 Input speed	≤15000rpm
电压(可选择) Voltage (optional)	3-24V	负载电流 Load current	300mA max

参考数据(马达定义值: 24V 6100rpm) 下表根据马达定义值测试, 数据只作为参考值。 Parameter (values at 24V & 6100rpm) The following data is for reference only.

型号 Model	Rated Speed 额定转速	Max Speed 最高转速	Max Rated Torque 额定容许力矩	Max. Intermittent Torque 瞬间容许力矩	Reduction Ratio 减速比	Gearbox Length 减速箱长 L1	Overall Length 总长 L
	rpm	rpm	gf.cm	gf.cm		mm	mm
MD038038-4	1525	7500	80000	240000	4	30.7	87.7
MD038038-6.25	976	4800	80000	240000	6.25		
MD038038-16	381	1875	80000	240000	16		
MD038038-25	244	1200	80000	240000	25		
MD038038-39	156	769	80000	240000	39		
MD038038-64	95	469	80000	240000	64		
MD038038-100	61	300	80000	240000	100		
MD038038-156	39	192	80000	240000	156		
MD038038-244	25	123	80000	240000	244		
MD038038-256	24	117	80000	240000	256		
MD038038-400	15	75	80000	240000	400		
MD038038-625	10	48	80000	240000	625		
MD038038-977	6	31	80000	240000	977		
MD038038-1526	4	20	80000	240000	1526		


注:可根据客户要求定制 Specifications can be customized per customer requirements.

PD行星齿轮箱

PD planetary gearbox

与MD行星齿轮箱对应的是PD行星齿轮箱, 相比之下, PD行星齿轮箱采用塑胶外壳, 在保证足够性能的前提下, 质量更轻, 噪音更低, 在消费电子、智能家居等产品中非常适用。

The PD planetary gearbox, with its lightweight plastic casing, offers reduced noise without compromising performance. It is ideal for consumer electronics and smart home products.



32
mm
塑料
Plastic

PD032032


齿轮箱规格 Gearbox Specifications

外径	Outer diameter	32mm	轴承	Bearing	含油轴承 oil-impregnated bearings	滚动轴承 Rolling bearing
材质	Material	塑料 Plastic	轴向窜动	Axial Play	≤0.3mm	≤0.3mm
旋转方向	Direction of rotation	cw & ccw	输出轴径向负载	Radial Load at Output Shaft	≤50N	≤100N
齿轮箱回程差	Backlash	≤3° 可定制 Customizable	工作温度	Operating temperature range	-20 ~ +75°C	

齿轮级数 Gearbox Stages

	2	3	4
减速比	16 / 23 / 33	67 / 94 / 133 / 188	272 / 383 / 541 / 764 / 1078
最大容许扭力(gf.cm)	Max rated torque of gearbox (gf.cm)	30000	30000
瞬间容许力矩(gf.cm)	Max. intermittent torque (gf.cm)	80000	80000
齿轮箱效率(%)	Gearbox efficiency (%)	73	65
长度(mm)	Gearbox length L1 (mm)	35.7	45.7
		55.7	

技术插图 | Technical Drawing



马达规格参数 Motor Specifications

马达(可选择) Motor type (optional)	直流有刷电机、直流无刷电机 Brushed DC motor, Brushless DC motor	输入速度 Input speed	≤12000rpm
电压(可选择) Voltage (optional)	3-24V	负载电流 Load current	300mA max

参考数据(马达定义值: 24V 7700rpm) 下表根据马达定义值测试, 数据只作为参考值。 Parameter (values at 24V & 7700rpm) The following data is for reference only.

型号 Model	Rated Speed 额定转速	Max Speed 最高转速	Max Rated Torque 额定容许力矩	Max. Intermittent Torque 瞬间容许力矩	Reduction Ratio 减速比	Gearbox Length 减速箱长 L1	Overall Length 总长 L
	rpm	rpm	gf.cm	gf.cm			
PD032032-16	469	1875	30000	80000	16	35.7	78.2
PD032032-23	313	1250	30000	80000	23		
PD032032-33	227	909	30000	80000	33		
PD032032-67	112	448	30000	80000	67	45.7	88.2
PD032032-94	80	319	30000	80000	94		
PD032032-133	56	226	30000	80000	133		
PD032032-188	40	160	30000	80000	188		
PD032032-272	28	110	30000	80000	272	55.7	98.2
PD032032-383	20	78	30000	80000	383		
PD032032-541	14	56	30000	80000	541		
PD032032-764	10	39	30000	80000	764		
PD032032-1078	7	28	30000	80000	1078		


注:可根据客户要求定制 Specifications can be customized per customer requirements.

零背隙齿轮箱

Zero backlash gearbox

针对一些非常需要精准定位的光学和高精度设备应用, 兆威零背隙齿轮箱, 凭借回程差接近零的精准度和及其高的传动效率, 为客户提供优秀的解决方案。

Designed for optical and high-precision equipment, this gearbox minimizes backlash (<1°) while delivering exceptional transmission efficiency.



GM20149-01


Φ16mm 正传动减速箱

主要参数

- 0.5W
- 0.1Nm
- 5.00N



技术插图



减速箱技术数据

级数	4
减速比	141.00
最大连续传输功率	W 0.50
最大瞬时传输功率	W 0.80
最大连续转矩	Nm 0.100
最大瞬时转矩	Nm 0.13
最高连续输入转速	rpm 12000
最高瞬时输入转速	rpm 15000
最大效率	% 65.00
空载平均空回	° 0.00
最大轴向动态载荷	N 5.00
最大径向载荷 (离法兰6.5mm处)	N 25.00
齿轮箱长度L1	mm 43.40
重量	G 41.00

*注：以上数据不包含电机，减速箱和电机整体出售，具体参数可根据客户要求定制。

推荐型号

型号	额定电压 (V)	空载数据		负载数据		总长 (mm)	齿轮箱额定容许力矩 (Nm)	齿轮箱瞬间容许力矩 (Nm)	减速比	减速箱长 L1(mm)	
		空载转速 (rpm)	空载电流 (mA max)	负载转速 (rpm)	负载电流 (mA Max)						
GM20149-01	12	90	22	50	120	1.00	43.4	0.100	0.200	141	43.4


*以上规格数据仅供参考，如有修改恕不另行通知，下单前请找客服咨询。

PL直角电机齿轮箱

PL Right-Angle Gear Motor

兆威PL直角电机通过齿轮箱和电机精巧结构，实现直角90°动力传输，凭借使用高性能材质，可工作于温度变化范围大和特殊的环境条件。

The PL right-angle gear motor achieves precise 90° power transmission by combinations of gearbox and motor design. Featuring high-performance materials, it is capable of operating in extreme temperatures and challenging environments.



MC正传动减速箱

MC Spur Gearbox

兆威MC正传动减速箱，采用正齿传动设计，结构简单的同时，还具有效率高，低背隙，低噪音，特别适用于轻载静音场景。

The MC spur gear transmission design ensures high efficiency, low backlash, and minimal noise with a simple structure, perfect for light-load and silent operation scenarios.



MC016


Φ16mm 正传动减速箱



主要参数

- 0.15~0.38W
- 0.01~0.12Nm
- 2.00N

技术插图



减速箱技术数据

级数	3	4	5	6	7
减速比	13、20	30、41、55	84、113、154	210、255、283、384	525、707、1064
最大连续传输功率 W	0.38	0.33	0.30	0.26	0.15
最大瞬时传输功率 W	1.14	0.99	0.90	0.78	0.45
最大连续转矩 Nm	0.01	0.025	0.05	0.12	0.12
最大瞬时转矩 Nm	0.03	0.075	0.15	0.36	0.36
最大效率 %	73.00	65.00	59.00	53.00	47.00
空载平均空回 °	1.50	1.50	1.50	1.50	1.50
最大轴向动态载荷 N	2.00	2.00	2.00	2.00	2.00
最大径向载荷 (离法兰4mm处) N	4.00	4.00	4.00	4.00	4.00
齿轮箱长度L1 mm	13.10	15.70	17.30	18.90	20.50
重量 G	16.00	16.50	17.00	17.50	18.00

*注：以上数据不含电机，减速箱和电机整体出售，具体参数可根据客户要求定制

推荐型号

型号	额定电压 (V)	空载数据		负载数据			总长 (mm)	齿轮箱额定容许力矩 (NM)	齿轮箱瞬时容许力矩 (NM)	减速比	减速箱长 L1(mm)
		空载转速(rpm)	空载电流(mA max)	负载转速(rpm)	负载电流(mA Max)	转矩(Kg.cm)					
MC016-13	5	534	120	390	320	0.10	31.7	0.010	0.030	13	13.1
MC016-20	5	360	120	300	320	0.10				20	
MC016-30	5	236	120	157	320	0.25	34.3	0.025	0.075	30	15.7
MC016-41	5	177	120	132	320	0.25				41	
MC016-55	5	130	120	110	320	0.25	35.9	0.050	0.150	55	17.3
MC016-84	5	83	120	60	320	0.50				84	
MC016-113	5	70	120	50	320	0.50	37.5	0.120	0.360	113	17.3
MC016-154	5	46	120	40	320	0.50				154	
MC016-210	5	34	120	22	320	1.20	39.1	0.120	0.360	210	18.9
MC016-255	5	28	120	20	320	1.20				255	
MC016-283	5	25	120	19	290	1.20				283	
MC016-384	5	19	120	15	270	1.20				384	
MC016-525	5	14	120	12	220	1.20	39.1	0.120	0.360	525	20.5
MC016-707	5	10	120	7	180	1.20				707	
MC016-1064	5	7	120	5	150	1.20				1064	

*以上规格数据仅供参考，如有修改恕不另行通知，下单前请找客户询问。

MC037E


Φ37mm 正传动减速箱

主要参数

- 5.5W
- 0.3~0.9Nm
- 300N



技术插图



减速箱技术数据

级数	3	4	5	6	7
减速比	23、33	49、79	106、152、214	288、414、584	785、1130
最大连续传输功率	W	5.50	5.50	5.50	5.50
最大瞬时传输功率	W	16.50	16.50	16.50	16.50
最大连续转矩	Nm	0.30	0.50	0.70	0.90
最大瞬时转矩	Nm	0.90	1.50	2.10	2.70
最大效率	%	73.00	65.00	59.00	53.00
空载平均空回	°	2.00	2.00	2.00	2.00
最大轴向动态载荷	N	300.00	300.00	300.00	300.00
最大径向载荷(离法兰4mm处)	N	10.00	10.00	10.00	10.00
齿轮箱长度L1	mm	21.60	24.20	26.80	29.40
重量	G	58.50	62.50	67.50	75.00
					79.50

*注：以上数据不包含电机，减速箱和电机整体出售，具体参数可根据客户要求定制

推荐型号

型号	额定电压 (V)	空载数据		负载数据			总长 (mm)	齿轮箱额定容许力矩 (NM)	齿轮箱瞬间容许力矩 (NM)	减速比	减速箱长 L1(mm)
		空载转速(rpm)	空载电流(mA max)	负载转速(rpm)	负载电流(mA Max)	转矩(Kg.cm)					
MC037E-23	12	250	150	182	700	3.0	53.25	0.30	0.90	23	21.6
MC037E-33	12	174	150	138	550	3.0				33	
MC037E-49	12	117	150	88	600	5.0	55.85	0.50	1.50	49	24.2
MC037E-79	12	73	150	65	400	5.0				79	
MC037E-106	12	54	150	48	650	7.0				106	
MC037E-152	12	38	150	35	500	7.0	58.45	0.70	2.10	152	26.8
MC037E-214	12	27	150	25	400	7.0				214	
MC037E-288	12	20	150	19	300	9.0				288	
MC037E-414	12	14	150	13	200	9.0	61.05	0.90	2.70	414	29.4
MC037E-584	12	10	150	10	150	9.0				584	
MC037E-785	12	7	150	7	150	9.0	63.65	0.90	2.70	785	32
MC037E-1130	12	5	150	5	150	9.0				1130	

*以上规格数据仅供参考，如有修改恕不另行通知，下单前请找客户询问。



MC系列无刷直流空心杯电机
MC brushless DC coreless motor



MP有刷直流电机
MP brushed DC motor



MC步进电机
MC stepper motor

电机

Micro Motor

兆威专注于微小驱动领域，采用高品质材料研发制造更强性能的微型电机，从原材料到组件都经过严苛选择和测试，以实现大功率密度、高精度和长使用寿命。其中包括无刷直流空心杯电机、有刷直流电机和步进电机、无刷直流电机。产品尺寸覆盖6mm至24mm直径范围，这些产品应用广泛，为满足高要求性，还可以根据客户要求进行优化和采用高品质材料，例如采用NdFeB的高转矩直流电机。

ZHAOWEI specializes in micro drive solutions, leveraging high-quality materials to develop and manufacture micro motors with superior performance. From raw materials to components, every element undergoes rigorous selection and testing to achieve high power density, precision, and longevity. The product lineup includes brushless DC coreless motors, brushed DC motors, stepper motors, brushless DC motors. These motors range in size from 6mm to 24mm in diameter and are widely applicable across various industries. To meet demanding requirements, products can be optimized and built with premium materials, such as high-torque DC motors utilizing NdFeB (Neodymium Iron Boron) magnets for enhanced performance.

MC系列无刷直流空心杯电机

MC Brushless DC Coreless Motors

兆威MC系列无刷直流空心杯电机结合了无刷直流电机技术和空心杯结构，拥有高转速，长寿命，过载能力强，尤其是基于设计的不同，实现长寿命，高效率，出色的控制性能，无齿槽转矩。

ZHAOWEI's MC Series Brushless DC Coreless Motors combine brushless DC motor technology with a coreless structure. Key features include high rotational speeds, long operational lifespan, strong overload capacity. The design ensures high efficiency, extended service life, and superior control performance, while eliminating cogging torque for smooth operation.



MC0623-01


Φ6mm 无刷, 空心杯电机

主要参数

- 两磁极
- 2W
- 46800rpm
- 0.4mNm



技术插图



电机数据 (额定值)

额定电压	V	12
空载转速	rpm	63400±10%
空载电流	A	37±50%
额定转速	rpm	46800±10%
额定转矩	mNm	0.4
额定电流	A	0.256±50%
堵转转矩	mNm	1.5±7%
堵转电流	A	0.85±20%
最大效率	%	63±7%

电机常数 (额定值)

相间电阻	Ω	14.4±10%
相间电感	mH	0.1±10%
转矩常数	mNm/A	1.73±20%
速度常数	rpm/V	5523±20%
转速/转矩斜度	rpm/mNm	45972±20%
机械时间常数	ms	2.84±20%
转子惯量	gcm ²	0.007±20%

热参数

机壳-环境热阻	K/W	67.9
绕组-机壳热阻	K/W	15.2
绕组热时间常数	s	1.54
电机热时间常数	s	71.5
环境温度	°C	-20~+100
最大绕组温度	°C	125

机械参数 (滚珠轴承)

最大允许转速 (rpm)	100 000
最大轴向间隙 (mm)	< 0.15 N 0
	> 0.15 N 0.06 (max)
径向间隙	preloaded
最大轴向动态载荷(N)	0.1
最大允许静止态载力 (N)	10
最大径向载荷, 距离法兰处2mm处(N)	2

备注：可根据客户要求定制

端子型号

Molex 52745-0897 52207-0460
FCI SFV8R-2STBE1HLF SFW4R-2STGE1LF

备注：可根据客户要求定制

端子定义


pin1	电机绕组1
pin2	电机绕组2
pin3	电机绕组3
pin4	VHall (3.3~24 VDC)
pin5	接地
pin6	霍尔传感器1
pin7	霍尔传感器2
pin8	霍尔传感器3

MC0824-01

Φ8mm 无刷, 空心杯电机

主要参数

- 两磁极
- 5.8W
- 25500rpm
- 0.85mNm

**技术插图****电机数据 (额定值)**

额定电压	V	12
空载转速	rpm	38500±10%
空载电流	A	70±50%
额定转速	rpm	25500±10%
额定转矩	mNm	0.85
额定电流	A	0.5±50%
堵转转矩	mNm	3.5±7%
堵转电流	A	1.65±20%
最大效率	%	67±7%

电机常数 (额定值)

相间电阻	Ω	8.4±10%
相间电感	mH	0.05±10%
转矩常数	mNm/A	2.22±20%
速度常数	rpm/V	3155±20%
转速/转矩斜度	rpm/mNm	11000±20%
机械时间常数	ms	2.87±20%
转子惯量	gcm²	0.024±20%

热参数

机壳-环境热阻	K/W	56.6
绕组-机壳热阻	K/W	11.5
绕组热时间常数	s	3.7
电机热时间常数	s	120
环境温度	°C	-20~+100
最大绕组温度	°C	125

机械参数 (滚珠轴承)

最大允许转速 (rpm)	40 000
最大轴向间隙 (mm)	< 0.15 N 0 > 0.15 N 0.06 (max)
径向间隙	preloaded
最大轴向动态载荷(N)	2
最大允许静动态载荷 (N)	10
最大径向载荷, 距离法兰处2mm处(N)	5

备注: 可根据客户要求定制

端子型号

Molex 52745-1297

备注: 可根据客户要求定制

端子定义


pin 1	电机绕组3
pin 2	电机绕组2
pin 3	电机绕组1
pin 4	接地
pin 5	VHall (3.3-24 VDC)
pin 6	霍尔传感器3
pin 7	霍尔传感器2
pin 8	霍尔传感器1
pin 9	空
pin 10	空
pin 11	空
pin 12	空

MC1028-01

Φ10mm 无刷, 空心杯电机

主要参数

- 两磁极
- 8.7W
- 26500rpm
- 1.5mNm

**技术插图****电机数据 (额定值)**

额定电压	V	12
空载转速	rpm	33000±10%
空载电流	A	80±50%
额定转速	rpm	26500±10%
额定转矩	mNm	1.5
额定电流	A	0.7±50%
堵转转矩	mNm	9±7%
堵转电流	A	2.75±20%
最大效率	%	71±7%

机械参数 (滚珠轴承)

最大允许转速 (rpm)	40 000
最大轴向间隙 (mm)	< 0.15 N 0 > 0.15 N 0.06 (max)
径向间隙	preloaded
最大轴向动态载荷(N)	2
最大允许静动态载荷 (N)	10
最大径向载荷, 距离法兰处2mm处(N)	5

备注: 可根据客户要求定制

端子型号

Molex 52745-1297

备注: 可根据客户要求定制

端子定义

pin 1	电机绕组3
pin 2	电机绕组2
pin 3	电机绕组1
pin 4	接地
pin 5	VHall (3.3-24 VDC)
pin 6	霍尔传感器3
pin 7	霍尔传感器2
pin 8	霍尔传感器1
pin 9	空
pin 10	空
pin 11	空
pin 12	空

MC1226-01


Φ12mm 无刷, 空心杯电机

主要参数

- 两磁极
- 9.9W
- 20970rpm
- 2.38mNm



技术插图



电机数据 (额定值)

额定电压	V	12
空载转速	rpm	28600±10%
空载电流	A	78±50%
额定转速	rpm	20970±10%
额定转矩	mNm	2.38
额定电流	A	0.69±50%
堵转转矩	mNm	8.9±7%
堵转电流	A	2.38±20%
最大效率	%	67±7%

电机常数 (额定值)

相间电阻	Ω	5.3±10%
相间电感	mH	0.042±10%
转矩常数	mNm/A	3.87±20%
速度常数	rpm/V	2383±20%
转速/转矩斜度	rpm/mNm	3213±20%
机械时间常数	ms	4.5±20%
转子惯量	gcm ²	0.138±20%

热参数

机壳-环境热阻	K/W	38.6
绕组-机壳热阻	K/W	7.5
绕组热时间常数	s	3.2
电机热时间常数	s	210
环境温度	°C	-20~+100
最大绕组温度	°C	125

机械参数 (滚珠轴承)

最大允许转速 (rpm)	40 000
最大轴向间隙 (mm)	< 0.15 N 0 > 0.15 N 0.06 (max)
径向间隙	preloaded
最大轴向动态载荷(N)	2
最大允许安静态装力 (N)	10
最大径向载荷, 距离法兰处2mm处(N)	5

备注: 可根据客户要求定制

端子型号

Molex 52745-0897 52207-0460
FCI SFV8R-2STBE1HLF SFW4R-2STGE1LF

备注: 可根据客户要求定制

端子定义

Pin1	电机绕组1
Pin2	电机绕组2
Pin3	电机绕组3
Pin4	VHall (3.3-24 VDC)
Pin5	接地
Pin6	霍尔传感器1
Pin7	霍尔传感器2
Pin8	霍尔传感器3

MP有刷直流电机

MP brushed DC motor

与传统电机不同, 兆威MC高转矩直流电机采用NdFeB, 具有非常高的磁能积和矫顽力, 可以在小空间下, 爆发出更强动力, 是汽车电子、工业自动化等众多行业的良选。

Unlike traditional motors, the MC High-Torque brushed DC Motor incorporates NdFeB magnets, known for their exceptional magnetic energy product and coercivity. This design delivers powerful performance in compact spaces, making it an ideal choice for industries such as automotive electronics and industrial automation.



MP1935-01


Φ19mm 石墨电刷, DC电机

主要参数

- 四磁极
- 4.5W
- 6700rpm
- 33mNm



技术插图



电机数据 (额定值)

额定电压	V	12
空载转速	rpm	8200 ± 10%
空载电流	A	0.3 (Max)
额定转速	rpm	6700 ± 10%
额定转矩	mNm	5.86
额定电流	A	0.55 ± 10%
堵转转矩	mNm	33 ± 7%
堵转电流	A	2.6 ± 10%
最大效率	%	65

电机常数 (额定值)

相间电阻	Ω	4.5 ± 10%
相间电感	mH	NA ± 10%
转矩常数	mNm/A	13.1 ± 20%
速度常数	rpm/V	684 ± 20%
转速/转矩斜度	rpm/mNm	243.5 ± 20%
机械时间常数	ms	NA ± 20%
转子惯量	gcm²	4 ± 20%

备注：可根据客户要求定制

MP2238-01


Φ22mm 石墨电刷, DC电机

主要参数

- 四磁极
- 11W
- 5300rpm
- 16.6mNm



技术插图



电机数据 (额定值)

额定电压	V	12
空载转速	rpm	6300 ± 10%
空载电流	A	0.3 (Max)
额定转速	rpm	5300 ± 10%
额定转矩	mNm	16.6
额定电流	A	1.20 ± 10%
堵转转矩	mNm	99.5 ± 7%
堵转电流	A	6.0 ± 10%
最大效率	%	65

电机常数 (额定值)

相间电阻	Ω	2.0 ± 10%
相间电感	mH	NA ± 10%
转矩常数	mNm/A	18 ± 20%
速度常数	rpm/V	525 ± 20%
转速/转矩斜度	rpm/mNm	63 ± 20%
机械时间常数	ms	NA ± 20%
转子惯量	gcm²	10 ± 20%

备注：可根据客户要求定制

MP2430-03


Φ24mm 石墨电刷, DC电机

主要参数

- 四磁极
- 11W
- 5100rpm
- 15.8mNm



技术插图



电机数据 (额定值)

额定电压	V	12
空载转速	rpm	6200 ± 10%
空载电流	A	0.4 (Max)
额定转速	rpm	5100 ± 10%
额定转矩	mNm	15.8
额定电流	A	1.2 ± 10%
堵转转矩	mNm	95 ± 7%
堵转电流	A	5.8 ± 10%
最大效率	%	65

电机常数 (额定值)

相间电阻	Ω	2 ± 10%
相间电感	mH	NA ± 10%
转矩常数	mNm/A	18 ± 20%
速度常数	rpm/V	515 ± 20%
转速/转矩斜度	rpm/mNm	65 ± 20%
机械时间常数	ms	NA ± 20%
转子惯量	gcm ²	10 ± 20%

备注：可根据客户要求定制

MC步进电机

MC stepper motor

兆威MC步进电机具有高精度, 加速迅捷的特点, 能够快速的达到最大输出功率, 无需编码器即可实现精确控制。

ZHAOWEI's MC Stepper Motors are characterized by high precision and rapid acceleration. They can quickly achieve maximum output power and provide precise control without requiring an encoder, making them highly efficient and reliable.



ZPM0809-20-002



Φ8mm 步进电机 (MC版)

主要参数

- 步进角 $18^\circ \pm 1^\circ$
- 相数 2相
- 励磁 2-2相



技术插图



电机数据 (额定值)

额定电压	V	5
最大牵引频率	pps	≥ 1800
最大牵出频率	pps	≥ 2400
牵引力矩	gf.cm	≥ 13 (200pps)
牵出力矩	gf.cm	≥ 15 (200pps)

电机常数 (额定值)

相间电阻	Ω	$7.5 \pm 10\%$
相间电感	mH	$1.6 \pm 30\%$


备注：可根据客户要求定制

端子型号

Molex 52745-1297


备注：可根据客户要求定制

典型应用产品数据



兆威拥有专业的电控研发和生产团队，开发编码器和电控板，其中编码器至少2~3通道，能够实现1~1024脉冲。而电控板则专为直流电机和无刷电机运转速度控制设计，工作模式和参数均可调整，产品通用性强，场景适用性广。

ZHAOWEI boasts a specialized team for electronic control system R&D and production. The portfolio includes encoders and control boards, ensuring optimal motor performance and versatility. The encoder has 2 to 3 Channels, delivering 1 to 1024 Pulses. Designed specifically for DC and brushless motors, the control boards allow adjustable operation modes and parameters. Their broad compatibility and versatility make them suitable for diverse applications.



CB-ST编码器
CB-ST encoder




电控板
Electronic control board

CB-ST编码器

CB-ST encoder


兆威采用磁编码器原理，通过传感磁体与电机轴保持同步，经霍尔传感器检测磁场变化，实现定位任务和精确的转速控制，对灰尘、湿气、振动、冷热温差具有很强抗干扰性。

The CB-ST Encoder uses magnetic encoding principles. By synchronizing the magnetic sensor with the motor shaft, the hall sensor detects magnetic field changes to accomplish precise positioning and speed control tasks. The encoder can remain accurate performance in demanding environments with high resistance to dust, moisture, vibration, and temperature fluctuations.



SM008008


Φ8mm 磁编



主要参数

- 10mA
- 3.3—5V
- 55000rpm

技术插图



技术参数

每旋转一周的脉冲数	N	1 ~ 1024
输出信号		方波 单端ABZ
电源电压	UDD	3.3~5 V
工作电流, 典型值	IDD	10mA
索引脉冲宽度	P0	180 ± 45°
A、B通道相位差	Φ	90 ± 45°
工作温度范围		-40~125°C
精度		±1
滞后角		0.088 °m

引脚定义


Pin1: U	Pin7: VCC
Pin2: U	Pin8: GND
Pin3: V	Pin9: A
Pin4: V	Pin10: B
Pin5: W	Pin11: Z
Pin6: W	Pin12: 无

SM012012


Φ12mm 磁编

主要参数

- 10mA
- 3.3—5V
- 55000rpm




技术插图



技术参数

每旋转一周的脉冲数	N	1 ~ 1024
输出信号	方波	差分ABZ/UVW
		单端ABZ
电源电压	UDD	3.3~5 V
工作电流, 典型值	IDD	10mA
索引脉冲宽度	P0	180 ± 45°
A、B通道相位差	Φ	90 ± 45°
工作温度范围		-40~125°C
精度		±1
滞后角		0.088 °m

引脚定义



SM022022


Φ22mm 磁编

主要参数

- 10mA
- 3.3—5V
- 55000rpm




技术插图



技术参数

每旋转一周的脉冲数	N	1 ~ 1024
输出信号	方波	差分ABZ/UVW
		单端ABZ
电源电压	UDD	3.3~5 V
工作电流, 典型值	IDD	10mA
索引脉冲宽度	P0	180 ± 45°
A、B通道相位差	Φ	90 ± 45°
工作温度范围		-40~125°C
精度		±1
滞后角		0.088 °m

引脚定义




SM038038


Φ38mm 磁编

主要参数

- 10mA
- 3.3—5V
- 55000rpm



技术插图



技术参数

每旋转一周的脉冲数	N	1 ~ 1024
输出信号	方波	差分ABZ/UVW 单端ABZ
电源电压	UDD	3.3~5 V
工作电流, 典型值	IDD	10mA
索引脉冲宽度	P0	180 ± 45°
A、B通道相位差	Φ	90 ± 45°
工作温度范围		-40~125°C
精度		±1
滞后角		0.088 °m

引脚定义


	PIN1: 无	PIN6: A
	PIN2: VCC	PIN7: B-
	PIN3: GND	PIN8: B
	PIN4: 无	PIN9: Z-
	PIN5: A-	PIN10: Z

电控板

Electronic Control Boards

电控板能够对微型电机实现高效控制，兆威专注于微型驱动领域，开发直流电机、无刷空心杯电机、步进电机等微型电机电控板，能够根据客户需求，精确地调节驱动功率，转速等，具有电机匹配度广、控制精确的特点。

ZHAOWEI develops high-performance control boards tailored for micro motors, including DC motors, brushless coreless motors, and stepper motors. These boards offer precise power and speed regulation based on client needs, broad motor compatibility, exceptional control accuracy.



PJ23144

通用工装驱动板及通用采集板

产品优势：


- 驱动器几乎支持市面上常见的电机，兼容性强；
- 采集卡兼容大多数PCBA板单板检测和强大的霍尔传感器信号质量检测，丰富的通信接口。



产品参数

重量	1KG					
适用电机	通用驱动器支持300W以下各种类型的电机驱动控制，如：直流有刷电机、步进电机、有感直流无刷电机、无感直流无刷电机；					
传感器	支持各种类型的位置传感器，如霍尔、ABZ/UVZ增量式模式磁编、IIC模式磁编、SPI模式磁编、PWM模式磁编；					
通信接口	持各种通信接口，如普通IO口、IIC通信、RS485、RS232、SPI、USART、PLC IO口、CAN、LINK					
信号质量检测	霍尔信号质量（低电平电压值、高电平电压值、频率、占空比、相位差）	电压检测	mA级待机电流检测	uA级低功耗检测		
电气数据	采集卡电源接口（14）	驱动器电源接口（6）：支持5~48V输入，电机驱动电压随输入电压				
	额定电压24V DC，最大电流2A	(1) 12V电源输出接口：支持0.5A电流向外部输出				
		(2) 5V电源输出接口：支持0.2A电流向外部输出				
		(3) 3.3V电源输出接口：支持0.2A电流向外部输出				
保护功能	输入防反接保护	过流保护	所有端口ESD防静电			
工作温度	-30~75°C					
尺寸						

采集卡接线图及参数



- (1) DAC输出接口: 0~10V
- (2) ADC检测接口: 0~36V
- (3) ADC检测接口: 0~24V
- (4) ADC检测接口: 0~12V
- (5) ADC检测接口: 0~5V
- (6) ADC检测接口: 0~48V
- (7) PWM信号检测通道4: 半桥驱动，MOS上管GS极PWM检测，最高电压≤20V
- (8) PWM信号检测通道3: 半桥驱动，MOS上管GS极PWM检测，最高电压≤20V

- (9) PWM信号检测通道2: 半桥驱动，MOS上管GS极PWM检测，最高电压≤20V

- (10) PWM信号检测通道1: 半桥驱动，MOS上管GS极PWM检测，最高电压≤20V

- (11) PWM信号检测4通道: MOS下管GS极PWM检测，最高电压≤60V

- (12) PWM信号检测8通道: MCU输出的PWM检测，最高电压≤60V

- (13) 霍尔接口: 支持3~24V霍尔电平输入检测；霍尔供电支持3~24V输出，无极调节

- (14) 电源接口: 额定电压24V DC，最大电流2A

- (15) PLC接口: 支持2路24V PLC信号输入；支持2路集电极开漏输出，驱动能力0.5A，最高电压150V

- (16) 扩展IO: 6路，3.3V电平

- (17) USART通信接口: 5V电平

- (18) RS-232通信接口:

- (19) CAN总线接口

- (20) RS-485通信接口

- (21) USART通信接口: 3.3V电平


- (22) IIC通信接口

- (23) LINK通信接口

- (24) TF存储卡卡槽

注意事项: RS-232、3.3V USART通信接口和5V USART通信接口不能同时通信，只能三选一

驱动器接口图及参数



- (1) SPI通信接口
- (2) 霍尔检测接口
- (3) PLC接口: 支持2路24V PLC信号输入；支持2路集电极开漏输出，驱动能力0.5A，最高电压150V
- (4) 电机接口: 直流有刷电机、步进电机、三相无刷电机
- (5) 扩展IO: 6路，3.3V电平
- (6) 电源接口: 支持5~48V输入，电机驱动电压随输入电压
- (7) 12V电源输出接口: 支持0.5A电流向外部输出
- (8) 5V电源输出接口: 支持0.2A电流向外部输出
- (9) 3.3V电源输出接口: 支持0.2A电流向外部输出
- (10) LINK通信接口
- (11) IIC通信接口
- (12) RS-485通信接口
- (13) USART通信接口: 5V电平
- (14) CAN总线接口
- (15) USART通信接口: 3.3V电平
- (16) RS-232通信接口
- (17) TF存储卡卡槽

团队文化

Company Culture



ZHAOWEI 兆威

微型驱动系统制造商
Micro Drive System Manufacturer

股票简称：兆威机电 股票代码：003021
Stock Abbreviation: ZHAOWEI Machinery & Electronics Stock Code: 003021